



5300 Beethoven Street, Los Angeles, CA 90066  
TEL: (310)306-5556 • FAX: (310)821-7413  
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## MODEL 5302034-800

**1.8—2.0 GHz**  
**50 WATTS**  
**LINEAR POWER RF AMPLIFIER**

### Solid State Band-specific High Power RF Amplifier

The 5302034-800 is a 50 Watt band-specific amplifier that covers the 1.8—2.0 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5302034-800 comes with an extended multiyear warranty.

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	1.8—2.0 GHz
2	Output Protection	Open and Short
3	Saturated Output Power	50 Watts minimum
4	Power Output @ 1dB Comp.	40 Watts min
5	Small Signal Gain	+48 dB min
6	Gain Flatness	± 2.0 dB max
7	IP <sub>3</sub>	+57 dBm typical
8	Input VSWR	2:1 max
9	Harmonics	-20 dBc typical @ 40 Watts
10	Spurious Signals	< -60 dBc typical @ 40 Watts
11	Input/Output Impedance	50 Ohms nominal
12	DC Input Current	10 Amps max
13	DC Input	13 VDC nominal
14	RF Input	+10 dBm max
15	RF Input Signal Format	CW/AM/FM/PM/Pulse
16	Class of Operation	A/AB
<b>Mechanical</b>		
17	Dimensions	6.55" x 4" x 1.1"
18	Weight	3 lb. max
19	Connectors	SMA female
20	Grounding	Chassis
21	Cooling	Adequate Heatsink Required
<b>Environmental</b>		
22	Baseplate Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



#### Output Protection:

Can operate into a full Open or Short, without damage, due to the use of an Internal Circulator and Load.

#### Shutdown:

+5V = Off  
Open or N/C = On

#### Forward Power Voltage Detector

#### Temperature Sensor Voltage out

Approved By: \_\_\_\_\_ Date: \_\_\_\_\_