

RP TNC Female Connector Crimp/Solder Attachment For RG58



TECHNICAL DATA SHEET

PE4686

RP TNC Female Connector Crimp/Solder Attachment For RG58

Configuration

Connector TNC Female Reverse Polarity

Connector Interface Type RG58
Cable Attachment Method (Shield/Contact) Crimp/Solder
Body Style Straight

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

DC to 11

1.50

50

1.500

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.43 [36.32]

 Width/Dia., in [mm]
 0.5 [13]

 Weight, lbs [q]
 0.034 [15.42]

Connector

Type TNC Female Reverse Polarity

Contact Material and Plating
Contact Plating Specification
Body Material and Plating
Body Plating Specification
Brass, Gold
30µ in. minimum
Brass, Nickel
100µ in. minimum

Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/tnc-female-reverse-polarity-rg58-connector-pe4686-p.aspx

RP TNC Female Connector Crimp/Solder Attachment For RG58 from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

