

5 Section Highpass Filter With SMA Female Connectors Operating From 30 MHz To 300 MHz With a 270 MHz Passband PASTERNACK 30 lo300 MHz DC. 1224

PE8717

TECHNICAL DATA SHEET

5 Section Highpass Filter With SMA Female Connectors Operating From 30 MHz To 300 MHz With a 270 MHz Passband

Configuration	
Connector 1	SMA Female
Connector 2	SMA Female
Passband Frequency Range, MHz	30 to 300
r assband r requency range, winz	50 10 500
Electrical Specifications	
Passband Minimum Frequency, MHz	30
Passband Maximum Frequency, MHz	300
Useable Frequency Range, MHz	DC to 300
Impedance, Ohms	50
Maximum Insertion Loss, dB	1
Passband Maximum VSWR	2:1
	5
Maximum Input Power, Watts	
Rejection at 15 MHz	60 dB
Rejection at 20 MHz	40 dB
Mechanical Specifications	
Size	
Length, in [mm]	1.7 [43.18]
Width, in [mm]	0.75 [19.05]
Height, in [mm]	0.65 [16.51]
	0.05 [10.51]
Connector 1	
Туре	SMA Female
Octometer 0	
Connector 2	SMA Female
Туре	SIMA Female
Compliance Certifications (visit www.Pasternack.com for current document)	
RoHS Compliant	Yes
None compliant	100
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
NUICES.	values at 20°C, sed level

URL: http://www.pasternack.com/5-section-high-pass-filter-30-mhz-300-mhz-passband-270-mhz-pe8717-p.aspx

5 Section Highpass Filter With SMA Female Connectors Operating From 30 MHz To 300 MHz With a 270 MHz Passband from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



5 Section Highpass Filter With SMA Female Connectors Operating From 30 MHz To 300 MHz With a 270 MHz Passband

