

# Keysight L4411A

## Low profile 6½ Digit Multimeter

Leading the Industry in High-Performance  
System Test

### Data Sheet



### Product Discontinuance Notice

The L4411A 1U high rack DMM and all associated options will be discontinued December 1, 2016. The last date this product can be ordered is November 30, 2016.

- For an alternate replacement product, Keysight recommends the 34465A, 6½ digit Truevolt DMM with high-speed option. Please note this is a 2U high DMM and will not fit into a 1U space.
- For more information, please visit [www.keysight.com/find/L4411A](http://www.keysight.com/find/L4411A)
- To contact a product selection expert, visit [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

# Introduction

## Keysight L4411A 6½-Digit High-Performance DMM

- 50,000 readings/sec @ 4½ digits direct to PC
- 10,000 readings/sec @ 5½ digits direct to PC
- 1,000 readings/sec @ 6½ digits direct to PC
- Analog level triggering
- Programmable pre/post triggering
- LAN extensions for instruments (LXI), USB & GPIB standard
- 30 PPM 1 year basic DC accuracy
- DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, period, and diode test
- Capacitance & temperature measurements
- Expanded measurement ranges

## A new standard for modular system DMMs

The L4411A 6½ digit high performance DMM expands the Keysight Technologies, Inc. industry leading offering of LXI system products. For the test system integrator looking for the next generation modular DMM, this new meter offers the industry's best measurement speed and throughput, a reduced size (1 rack unit high), superior measurement performance, and a choice of computer interfaces, including LXI, providing high performance, easy to use, economical I/O. A simple display, including 'latest reading' and LAN address, allows the system integrator to quickly integrate and debug the test system. And finally, the DMM comes with a compatibility mode, requiring little-to-no code change to upgrade your test system with next generation capabilities.

## Dramatic system performance

Whether it's raw reading speed or fast system throughput, the L4411A sets a new benchmark in performance. Using a new A/D technology, the L4411A achieves an impressive 50,000 readings a second at 4½ digits, and can stream readings to your computer at this same speed! Transactional I/O (single reading—measurement and PC transfer time) is 3x faster than other popular modular DMMs, significantly enhancing your test throughput. Triggering is fast and precise, with both trigger latency and trigger jitter less than 1 µs, while bus query response is less than 500 µs. ACV measurements are faster as well thanks to a digital measurement technique that additionally improves accuracy at high and low frequencies.

## LXI-Class C

LAN Extensions for Instruments (LXI) provides the next generation I/O for system applications requiring high throughput. Transfer rates of over 250,000 readings/sec are attainable ensuring even the most data intensive measurements are fast, without the overhead cost of an instrument mainframe. LXI provides a built-in Graphical Web Interface that allows you to interactively control the DMM without the hassle of programming, making it great for debugging your system. The L4411A DMM is LXI – Class C compliant.

### Enhanced measurement capabilities

The L4411A offers temperature and capacitance capabilities in addition to those measurements you have come to expect such as DCV, ACV, DCI, ACI, 2-wire and 4-wire resistance, frequency, period and diode test. You also get offset compensated Ohms, allowing you to accurately measure resistance in the presence of voltages. Measurement ranges have been expanded as well; for example, DC and AC current ranges now go down to 100  $\mu$ A, resulting in 100 pA resolution. Real-time math and statistics are included, and a peak-detect capability allows you to capture peaks as short as 20  $\mu$ s.

### System integration

When deciding on your next system DMM you can't go wrong with the L4411A. Choose from LAN (LXI), USB or GPIB interfaces, all standard on the L4411A, to connect to your computer. The 1U size is perfect for space constrained applications like aerospace/defense depot test. Concerned about the viability of your existing software programs? This new DMM responds to standard

commands for programmable instrumentation (SCPI). Additionally there is a 34401A/E1412A emulation mode to ensure the easiest upgrade possible, virtually eliminating costly software and documentation changes. The autoranging power supply allows you to connect to any input power without selecting input voltages or changing fuses. Keysight's I/O Library Suite ships with the L4411A to help you quickly establish an error-free connection between your PC and instrument. It provides robust instrument control and works with the software development environment you choose.

### Companion LXI switch modules

Need a switch to route your signal to the L4411A? Consider Keysight's LXI switch modules. Choose from a 40-channel armature relay multiplexer (L4421A), a dual/quad 4x8 reed relay matrix (L4433A) or a 32-channel Form A/C general purpose relay switch module (L4437A). Additionally, Keysight has LXI DAC, digital I/O and multi-function modules to help complete your test system requirements. All from the leader in LXI instrumentation, Keysight.


### Built to last

Our new DMM was designed to high standards of ruggedness and reliability. From the robust, compact package to careful selection of components and conservative circuit design, this meter is built to last. Calculated mean time between failure (MTBF) is in excess of 100,000 hours. Backed by a 3-year warranty and a worldwide network of service centers, you can buy with confidence.

### Go to the web

For the latest information on these or other Keysight DMMs, go to [www.keysight.com/find/dmm](http://www.keysight.com/find/dmm)

DMM dimensions (mm)



## Accuracy Specifications $\pm$ (% of reading + % of range)<sup>1</sup>


| Function                        | Range <sup>3</sup>                   | Frequency,<br>test current or<br>burden voltage | 24 hour <sup>2</sup><br>Tcal $\pm 1^\circ\text{C}$ | 90 day<br>Tcal $\pm 5^\circ\text{C}$ | 1 year<br>Tcal $\pm 5^\circ\text{C}$ | Temperature coefficient/ $^\circ\text{C}$<br>0 $^\circ\text{C}$ to (Tcal - 5 $^\circ\text{C}$ )<br>(Tcal + 5 $^\circ\text{C}$ ) to 55 $^\circ\text{C}$ |
|---------------------------------|--------------------------------------|-------------------------------------------------|----------------------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DC voltage</b>               | 100.0000 mV                          |                                                 | 0.0030 + 0.0030                                    | 0.0040 + 0.0035                      | 0.0050 + 0.0035                      | 0.0005 + 0.0005                                                                                                                                        |
|                                 | 1.000000 V                           |                                                 | 0.0020 + 0.0006                                    | 0.0030 + 0.0007                      | 0.0035 + 0.0007                      | 0.0005 + 0.0001                                                                                                                                        |
|                                 | <b>10.00000 V</b>                    |                                                 | <b>0.0015 + 0.0004</b>                             | <b>0.0020 + 0.0005</b>               | <b>0.0030 + 0.0005</b>               | <b>0.0005 + 0.0001</b>                                                                                                                                 |
|                                 | 100.0000 V                           |                                                 | 0.0020 + 0.0006                                    | 0.0035 + 0.0006                      | 0.0040 + 0.0060                      | 0.0005 + 0.0001                                                                                                                                        |
|                                 | 1000.000 V <sup>4</sup>              |                                                 | 0.0020 + 0.0006                                    | 0.0035 + 0.0006                      | 0.0040 + 0.0060                      | 0.0005 + 0.0001                                                                                                                                        |
| <b>True RMS</b>                 | 100.0000 mV                          | 3 Hz - 5 Hz                                     | 0.50 + 0.02                                        | 0.50 + 0.03                          | 0.50 + 0.03                          | 0.010 + 0.003                                                                                                                                          |
| <b>AC voltage</b> <sup>5</sup>  | to 750.000 V                         | 5 Hz - 10 Hz                                    | 0.10 + 0.02                                        | 0.10 + 0.03                          | 0.10 + 0.03                          | 0.008 + 0.003                                                                                                                                          |
|                                 |                                      | <b>10 Hz - 20 kHz</b>                           | <b>0.02 + 0.02</b>                                 | <b>0.04 + 0.02</b>                   | <b>0.045 + 0.02</b>                  | <b>0.005 + 0.002</b>                                                                                                                                   |
|                                 |                                      | 20 kHz - 50 kHz                                 | 0.04 + 0.025                                       | 0.08 + 0.025                         | 0.090 + 0.025                        | 0.010 + 0.0025                                                                                                                                         |
|                                 |                                      | 50 kHz - 100 kHz                                | 0.10 + 0.040                                       | 0.20 + 0.040                         | 0.200 + 0.040                        | 0.020 + 0.0040                                                                                                                                         |
|                                 |                                      | 100 kHz - 300 kHz                               | 1.00 + 0.250                                       | 1.20 + 0.250                         | 1.200 + 0.250                        | 0.120 + 0.0200                                                                                                                                         |
| <b>Resistance</b> <sup>6</sup>  | 100.0000 $\Omega$                    | 1 mA                                            | 0.0030 + 0.0030                                    | 0.008 + 0.004                        | 0.010 + 0.004                        | 0.0006 + 0.0005                                                                                                                                        |
|                                 | 1.000000 k $\Omega$                  | 1 mA                                            | 0.0020 + 0.0005                                    | 0.007 + 0.001                        | 0.010 + 0.001                        | 0.0006 + 0.0001                                                                                                                                        |
|                                 | <b>10.00000 k<math>\Omega</math></b> | <b>100 <math>\mu\text{A}</math></b>             | <b>0.0020 + 0.0005</b>                             | <b>0.007 + 0.001</b>                 | <b>0.010 + 0.001</b>                 | <b>0.0006 + 0.0001</b>                                                                                                                                 |
|                                 | 100.0000 k $\Omega$                  | 10 $\mu\text{A}$                                | 0.0020 + 0.0005                                    | 0.010 + 0.001                        | 0.012 + 0.001                        | 0.0006 + 0.0001                                                                                                                                        |
|                                 | 1.000000 M $\Omega$                  | 5 $\mu\text{A}$                                 | 0.0020 + 0.0010                                    | 0.030 + 0.001                        | 0.040 + 0.001                        | 0.0010 + 0.0002                                                                                                                                        |
|                                 | 10.00000 M $\Omega$                  | 500 nA                                          | 0.0100 + 0.0010                                    | 0.600 + 0.001                        | 0.800 + 0.001                        | 0.0030 + 0.0004                                                                                                                                        |
|                                 | 100.0000 M $\Omega$                  | 500 nA $\parallel$ 10 M $\Omega$                | 0.200 + 0.001                                      | 6.000 + 0.001                        | 8.000 + 0.001                        | 0.1000 + 0.0001                                                                                                                                        |
|                                 | 1.000000 G $\Omega$                  | 500 nA $\parallel$ 10 M $\Omega$                | 2.000 + 0.001                                      |                                      |                                      | 1.0000 + 0.0001                                                                                                                                        |
| <b>DC current</b>               | 100.0000 $\mu\text{A}$               | < 0.03 V                                        | 0.010 + 0.020                                      | 0.040 + 0.025                        | 0.050 + 0.025                        | 0.0020 + 0.0030                                                                                                                                        |
|                                 | 1.000000 mA                          | < 0.30 V                                        | 0.007 + 0.006                                      | 0.030 + 0.006                        | 0.050 + 0.006                        | 0.0020 + 0.0005                                                                                                                                        |
|                                 | 10.00000 mA                          | < 0.03 V                                        | 0.007 + 0.020                                      | 0.030 + 0.020                        | 0.050 + 0.020                        | 0.0020 + 0.0020                                                                                                                                        |
|                                 | 100.0000 mA                          | < 0.30 V                                        | 0.010 + 0.004                                      | 0.030 + 0.005                        | 0.050 + 0.005                        | 0.0020 + 0.0005                                                                                                                                        |
|                                 | 1.000000 A                           | < 0.80 V                                        | 0.050 + 0.006                                      | 0.080 + 0.010                        | 0.100 + 0.010                        | 0.0050 + 0.0010                                                                                                                                        |
|                                 | 3.000000 A                           | < 2.0 V                                         | 0.100 + 0.020                                      | 0.120 + 0.020                        | 0.150 + 0.020                        | 0.0050 + 0.002                                                                                                                                         |
| <b>True RMS</b>                 | 100.0000 $\mu\text{A}$               | <b>3 Hz - 5 kHz</b>                             | <b>0.10 + 0.04</b>                                 | <b>0.10 + 0.04</b>                   | <b>0.10 + 0.04</b>                   | <b>0.015 + 0.006</b>                                                                                                                                   |
| <b>AC current</b> <sup>7</sup>  | to 3.00000 A                         | 5 kHz - 10 kHz                                  | 0.20 + 0.04                                        | 0.20 + 0.04                          | 0.20 + 0.04                          | 0.030 + 0.006                                                                                                                                          |
| <b>Frequency<br/>or period</b>  | 100 mV                               | 3 Hz - 5 Hz                                     | 0.070 + 0.000                                      | 0.070 + 0.000                        | 0.070 + 0.000                        | 0.005 + 0.000                                                                                                                                          |
|                                 | to 750 V                             | 5 Hz - 10 Hz                                    | 0.040 + 0.000                                      | 0.040 + 0.000                        | 0.040 + 0.000                        | 0.005 + 0.000                                                                                                                                          |
|                                 |                                      | 10 Hz - 40 Hz                                   | 0.020 + 0.000                                      | 0.020 + 0.000                        | 0.020 + 0.000                        | 0.001 + 0.000                                                                                                                                          |
|                                 |                                      | <b>40 Hz - 300 kHz</b>                          | <b>0.005 + 0.000</b>                               | <b>0.006 + 0.000</b>                 | <b>0.007 + 0.000</b>                 | <b>0.001 + 0.000</b>                                                                                                                                   |
| <b>Capacitance</b> <sup>8</sup> | 1.0000 nF                            | 500 nA                                          | 0.50 + 0.50                                        | 0.50 + 0.50                          | 0.50 + 0.50                          | 0.05 + 0.05                                                                                                                                            |
|                                 | 10.000 nF                            | 1 $\mu\text{A}$                                 | 0.40 + 0.10                                        | 0.40 + 0.10                          | 0.40 + 0.10                          | 0.05 + 0.01                                                                                                                                            |
|                                 | 100.00 nF                            | 10 $\mu\text{A}$                                | 0.40 + 0.10                                        | 0.40 + 0.10                          | 0.40 + 0.10                          | 0.01 + 0.01                                                                                                                                            |
|                                 | 1.0000 $\mu\text{F}$                 | 10 $\mu\text{A}$                                | 0.40 + 0.10                                        | 0.40 + 0.10                          | 0.40 + 0.10                          | 0.01 + 0.01                                                                                                                                            |
|                                 | 10.000 $\mu\text{F}$                 | 100 $\mu\text{A}$                               | 0.40 + 0.10                                        | 0.40 + 0.10                          | 0.40 + 0.10                          | 0.01 + 0.01                                                                                                                                            |
| <b>Temperature</b> <sup>9</sup> |                                      |                                                 |                                                    |                                      |                                      |                                                                                                                                                        |
|                                 | <b>RTD</b>                           | -200 $^\circ\text{C}$ to 600 $^\circ\text{C}$   |                                                    | 0.06 $^\circ\text{C}$                | 0.06 $^\circ\text{C}$                | 0.003 $^\circ\text{C}$                                                                                                                                 |
|                                 | <b>Thermistor</b>                    | -80 $^\circ\text{C}$ to 150 $^\circ\text{C}$    |                                                    | 0.08 $^\circ\text{C}$                | 0.08 $^\circ\text{C}$                | 0.002 $^\circ\text{C}$                                                                                                                                 |
| <b>Diode test</b> <sup>10</sup> | 1.0000 V                             | 1 mA                                            | 0.002 + 0.010                                      | 0.008 + 0.020                        | 0.010 + 0.020                        | 0.0010 + 0.0020                                                                                                                                        |

1. Specifications are for 90 minute warm-up and 100 PLC.
2. Relative to calibration standards.
3. 20% overrange on all ranges, except DCV 1000 V, ACV 750 V, DCI and ACI 3 A ranges.
4. For each additional volt over  $\pm 500$  V add 0.02 mV of error.
5. Specifications are for sinewave input  $> 0.3\%$  of range and  $> 1$  mVrms. Add 30  $\mu\text{V}$  error for frequencies below 1 kHz. 750 VAC range limited to  $8 \times 10^7$  Volts-Hz. For each additional volt over 300 Vrms add 0.7 mVrms of error.
6. Specifications are for 4-wire resistance measurements, or 2-wire using Math Null. Without Math Null, add 0.2  $\Omega$  additional error in 2-wire resistance measurements.

7. Specifications are for sinewave input  $> 1\%$  of range and  $> 10$   $\mu\text{Arms}$ . Frequencies  $> 5$  kHz are typical for 1 A and 3 A ranges.
8. Specifications are for 1-hour warm-up using Math Null. Additional errors may occur for non-film capacitors.
9. For total measurement accuracy, add temperature probe error
10. Accuracy specifications are for the voltage measured at the input terminals only. 1 mA test current is typical. Variation in the current source will create some variation in the voltage drop across a diode junction.

## A-to-D converter noise performance

| Integration time<br>(NPLC) | Resolution<br>(ppm of range) <sup>1</sup> | Normal mode<br>rejection (dB) <sup>2</sup> | Readings/<br>second <sup>4</sup> |
|----------------------------|-------------------------------------------|--------------------------------------------|----------------------------------|
| 0.001                      | 30                                        | 0                                          | 50,000                           |
| 0.002                      | 15                                        | 0                                          | 25,000                           |
| 0.006                      | 6                                         | 0                                          | 10,000                           |
| 0.02                       | 3                                         | 0                                          | 3,000                            |
| 0.06                       | 1.5                                       | 0                                          | 1,000                            |
| 0.2                        | 0.7                                       | 0                                          | 300                              |
| 1                          | 0.3                                       | 55                                         | 60 (50)                          |
| 2                          | 0.2                                       | 110 <sup>3</sup>                           | 30 (25)                          |
| 10                         | 0.1                                       | 110 <sup>3</sup>                           | 6 (5)                            |
| 100                        | 0.03                                      | 110 <sup>3</sup>                           | 0.6 (0.5)                        |



1. Resolution is defined as the typical DCV 10 V range RMS noise. Auto-zero on for NPLC  $\geq 1$ . See manual for additional noise characteristics.
2. Normal mode rejection for power line frequency  $\pm 0.1\%$ .
3. For power-line frequency  $\pm 1\%$  75 dB and for  $\pm 3\%$  55 dB.
4. Maximum rate with auto-zero off for 60 Hz and (50 Hz) operation.

## System reading and throughput rates

DMM memory to PC (maximum reading rate out of memory)<sup>5</sup>

Drawing – Path B


| Reading format       | GPIB<br>readings/sec | USB 2.0<br>readings/sec | LAN (VXI-11)<br>readings/sec | LAN (sockets)<br>readings/sec |
|----------------------|----------------------|-------------------------|------------------------------|-------------------------------|
| <b>ASCII</b>         | 4,000                | 8,500                   | 7,000                        | 8,500                         |
| <b>32-bit binary</b> | 89,000               | 265,000                 | 110,000                      | 270,000                       |
| <b>64-bit binary</b> | 47,000               | 154,000                 | 60,000                       | 160,000                       |

Direct I/O measurements (single reading – measure and I/O time)<sup>5</sup> Drawing – Path C

| Function                         | Resolution<br>(NPLC)     | GPIB<br>msec | USB<br>2.0<br>msec | LAN<br>(VXI-11)<br>msec | LAN<br>(sockets)<br>msec | Maximum reading<br>rate into memory<br>or to direct I/O<br>(readings/sec)<br>Drawing-Path A or C |
|----------------------------------|--------------------------|--------------|--------------------|-------------------------|--------------------------|--------------------------------------------------------------------------------------------------|
| <b>DCV/2-wire<br/>resistance</b> | 0.001                    | 2.6          | 2.9                | 4.6                     | 3.2                      | 50,000                                                                                           |
| <b>ACV/<br/>frequency</b>        | Fast filter<br>1 ms gate | 10.0         | 10.0               | 10.0                    | 10.0                     | 500                                                                                              |

5. ½ scale input signal, immediate trigger, trigger delay 0, auto-zero off, auto-range off, no math, null off, 60 Hz line frequency. See manual for performance on other functions.

System reading architecture



## System performance

|                                  | Function<br>change<br>(msec) <sup>5</sup> | Range change<br>LAN/GPIB<br>(msec) <sup>6</sup> | Auto-range<br>(msec) <sup>7</sup> | Maximum<br>external<br>trigger rate | Maximum<br>internal<br>trigger rate |
|----------------------------------|-------------------------------------------|-------------------------------------------------|-----------------------------------|-------------------------------------|-------------------------------------|
| <b>DCV/2-wire<br/>resistance</b> | 22                                        | 3.9/2.6                                         | 7.5                               | 5,000/s                             | 50,000/s                            |
| <b>ACV/frequency</b>             | 37                                        | 6.5/6.4                                         | 19                                | 500/s                               | 500/s                               |

6. Time to change from 2-wire resistance to this specified function, or DCV to 2-wire resistance using the SCPI "FUNC" command.
7. Time to change from one range to the next higher range,  $\leq 10$  V,  $\leq 10$  MΩ.
8. Time to automatically change one range and be ready for the new measurement,  $\leq 10$  V,  $\leq 10$  MΩ.

## Measurement Characteristics

| DC voltage                     |                                                                                                                                |                               |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| Measurement method:            | Continuously integrating multi-slope IV A/D converter                                                                          |                               |
| Linearity: (10 V range)        | 0.0002% of reading<br>+ 0.0001% of range                                                                                       |                               |
| Input resistance:              | 0.1 V, 1 V, 10 V ranges                                                                                                        | 10 MΩ or > 10 GΩ (selectable) |
|                                | 100 V, 1000 V ranges                                                                                                           | 10 MΩ ± 1% (fixed)            |
| Input bias current:            | < 50 pA at 25 °C                                                                                                               |                               |
| Input protection:              | 1000 V                                                                                                                         |                               |
| DC CMRR:                       | 140 dB <sup>1</sup>                                                                                                            |                               |
| True RMS AC voltage            |                                                                                                                                |                               |
| Measurement method:            | AC-coupled True RMS measurement.<br>Digital sampling with anti-alias filter.                                                   |                               |
| Crest factor:                  | No additional error for crest factors < 10.<br>Limited by peak input and 300 kHz bandwidth.                                    |                               |
| Peak input:                    | 300% of range or 1100 V                                                                                                        |                               |
| Overload ranging:              | Will select higher range if peak input overload is detected during auto range.<br>Overload is reported in manual ranging.      |                               |
| AC CMR:                        | 70 dB <sup>2</sup>                                                                                                             |                               |
| Maximum input:                 | 400 Vdc, 1100 Vpk                                                                                                              |                               |
| Input impedance:               | 1 MΩ ± 2% in parallel with < 150 pF                                                                                            |                               |
| Input protection:              | 750 Vrms all ranges                                                                                                            |                               |
| Resistance                     |                                                                                                                                |                               |
| Measurement method:            | Selectable 2-wire or 4-wire.<br>Current source referenced to LO input.                                                         |                               |
| Offset compensation:           | Selectable on the 100 Ω, 1 kΩ, and 10 kΩ ranges                                                                                |                               |
| Max. lead resistance (4-wire): | 10% of range per lead for 100 Ω, 1 kΩ, 1 kΩ per lead on all other ranges                                                       |                               |
| Input protection:              | 1000 V on all ranges                                                                                                           |                               |
| DC current                     |                                                                                                                                |                               |
| Current shunt:                 | 200 Ω for 100 μA, 1 mA<br>2 Ω for 10 mA, 100 mA<br>0.1 Ω for 1 A, 3 A                                                          |                               |
| Input protection:              | 3 A, 250 V fuse                                                                                                                |                               |
| True RMS AC current            |                                                                                                                                |                               |
| Measurement method:            | AC-coupled true RMS measurement.<br>Directly coupled to the fuse and shunt.<br>Digital sampling with anti-alias filter.        |                               |
| Current shunt:                 | 200 Ω for 100 μA, 1 mA<br>2 Ω for 10 mA, 100 mA<br>0.1 Ω for 1 A, 3 A                                                          |                               |
| Maximum input:                 | The peak value of the DC + AC current must be < 300% of range. The RMS current must be < 3 A including the DC current content. |                               |

| Frequency and period          |                                                                                            |      |      |  |  |  |
|-------------------------------|--------------------------------------------------------------------------------------------|------|------|--|--|--|
| Measurement method:           | Reciprocal-counting technique. AC-coupled input using the AC voltage measurement function. |      |      |  |  |  |
| Input impedance:              | 1 MΩ ± 2% in parallel with < 150 pF                                                        |      |      |  |  |  |
| Input protection:             | 750 Vrms all ranges                                                                        |      |      |  |  |  |
| Capacitance                   |                                                                                            |      |      |  |  |  |
| Measurement method:           | Current input with measurement of resulting ramp.                                          |      |      |  |  |  |
| Connection type:              | 2-wire                                                                                     |      |      |  |  |  |
| Temperature                   |                                                                                            |      |      |  |  |  |
| Thermistor:                   | 2.2 kΩ, 5 kΩ, and 10 kΩ                                                                    |      |      |  |  |  |
| RTD:                          | $\alpha = 0.00385$<br>Ro from 49 Ω to 2.1 kΩ                                               |      |      |  |  |  |
| Diode test                    |                                                                                            |      |      |  |  |  |
| Response time:                | 300 samples/sec                                                                            |      |      |  |  |  |
| Continuity threshold:         | Fixed at 10 Ω                                                                              |      |      |  |  |  |
| Operating characteristics     |                                                                                            |      |      |  |  |  |
| Maximum readings/second       |                                                                                            |      |      |  |  |  |
| Digits                        |                                                                                            |      |      |  |  |  |
| Function 3                    | 4.5                                                                                        | 5.5  | 6.5  |  |  |  |
| DCV                           | 50 k                                                                                       | 10 k | 1 k  |  |  |  |
| 2-wire Ω                      | 50 k                                                                                       | 10 k | 1 k  |  |  |  |
| DCI                           | 50 k                                                                                       | 10 k | 1 k  |  |  |  |
| Frequency                     | 500                                                                                        | 90   | 10   |  |  |  |
| Period                        | 500                                                                                        | 90   | 10   |  |  |  |
| Filter setting                | fast                                                                                       | med  | slow |  |  |  |
| ACV                           | 500                                                                                        | 150  | 50   |  |  |  |
| ACI                           | 500                                                                                        | 150  | 50   |  |  |  |
| Additional specifications     |                                                                                            |      |      |  |  |  |
| Resolution:                   | See table on page 5                                                                        |      |      |  |  |  |
| Overall bandwidth, DCV & DCI: | 15 kHz typical @ 20 μs aperture (-3 dB)                                                    |      |      |  |  |  |
| Triggering:                   | Pre/Post, Analog Level, Int/Ext, Pos/Neg                                                   |      |      |  |  |  |
| Timebase resolution:          | 19.9524 μs 0.01% accuracy                                                                  |      |      |  |  |  |
| Trigger jitter:               | 2 μs (p-p), 20 μs (p-p) when pre-triggered                                                 |      |      |  |  |  |

1. For 1 kΩ unbalanced in LO lead, ± 500 V peak maximum
2. For 1 kΩ unbalanced in LO lead and < 60 Hz, ± 500 V peak maximum
3. Maximum rate for DCV, DCI, and resistance functions (using zero settling delay, autozero off, manual range)

## Ordering Information

### Keysight L4411A Multimeter

#### Accessories included

Test report, power cord, LAN cross-over interface cable.

Product reference CD-ROM (34410-13601):

- Software
  - IntuiLink software
  - IVI-COM driver
  - LabView driver
  - Example programs
- Online documentation
  - Programmer's reference
  - Getting started guide
  - User's guide
  - Service guide
  - Localized manuals

Keysight I/O Libraries CD-ROM (E2094-60003)

#### Options

Opt. 001 Front measurement terminals ONLY

Opt. A6J ANSI Z540 compliant calibration

#### Keysight accessories

- Y1133A Measurement & trigger cable kit
- Y1160A Rack mount kit for L4400A series instruments  
racks 1 or 2 instruments side-by-side on  
sliding tray
- 11059A Kelvin probe set
- 11060A Surface mount device (SMD) test probes
- 11062A Kelvin clip set
- 34134A DC coupled current probe
- 34136A High voltage probe
- 34138A Test lead set
- 34171B Input terminal connector (sold in pairs)
- 34172B Input calibration short (sold in pairs)
- 34330A 30 A current shunt
- E2308A 5 kΩ thermistor probe

| Spurious-free dynamic range & signal to noise distortion ratio |                                                                                                                                                                                     |           |       |
|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
| Function                                                       | Range                                                                                                                                                                               | Spur-free | SNDR  |
| DCV                                                            | 1 V                                                                                                                                                                                 | -75 dB    | 60 dB |
|                                                                | 10 V <sup>1</sup>                                                                                                                                                                   | -70 dB    | 60 dB |
|                                                                | 100 V                                                                                                                                                                               | -75 dB    | 60 dB |
| 1. 1.                                                          | 10 V range: 2 V (p-p) <signal< 16 V (p-p)                                                                                                                                           |           |       |
| Triggering and memory                                          |                                                                                                                                                                                     |           |       |
| Reading hold sensitivity:                                      | 1% of reading                                                                                                                                                                       |           |       |
| Samples per trigger:                                           | 1 to 1,000,000                                                                                                                                                                      |           |       |
| Trigger delay:                                                 | 0 to 3600 sec (20 µs step size)                                                                                                                                                     |           |       |
| External trigger:                                              | Programmable edge, low-power TTL compatible                                                                                                                                         |           |       |
| Delay:                                                         | < 1 µs                                                                                                                                                                              |           |       |
| Jitter:                                                        | < 1 µs                                                                                                                                                                              |           |       |
| Max rate:                                                      | 5,000/sec                                                                                                                                                                           |           |       |
| Min pulse width:                                               | 1 µs                                                                                                                                                                                |           |       |
| Voltmeter complete:                                            | 3 V logic output, 2 µs pulse with programmable edge                                                                                                                                 |           |       |
| Nonvolatile memory:                                            | 50,000 readings                                                                                                                                                                     |           |       |
| Volatile memory:                                               | 1,000,000 readings                                                                                                                                                                  |           |       |
| Sample timer:                                                  |                                                                                                                                                                                     |           |       |
| Range:                                                         | 0 to 3600 s (20 µs step sizes)                                                                                                                                                      |           |       |
| Jitter:                                                        | < 100 ns                                                                                                                                                                            |           |       |
| General specifications                                         |                                                                                                                                                                                     |           |       |
| Power supply:                                                  | 90 V – 264 V @ 45-66 Hz                                                                                                                                                             |           |       |
|                                                                | 90 V – 134 V @ 360 – 440 Hz                                                                                                                                                         |           |       |
| Power line frequency:                                          | Automatically sensed at power-on                                                                                                                                                    |           |       |
| Power consumption:                                             | 50 VA peak (18 W average)                                                                                                                                                           |           |       |
| Operating environment:                                         | Full accuracy for 0 °C to 55 °C,<br>80% R.H. at 40 °C non-condensing                                                                                                                |           |       |
| Storage temperature:                                           | -40 °C to 70 °C                                                                                                                                                                     |           |       |
| Weight:                                                        | 1.9 kg (4.25 Lbs)                                                                                                                                                                   |           |       |
| Dimensions:                                                    | (W x H x D) 40.9 mm x 212.3 mm x 363.2 mm                                                                                                                                           |           |       |
| Safety:                                                        | IEC 61010-1, EN 61010-1, UL 61010-1, CAN/CSA-C22.2 No. 61010-1, refer to Declarations of Conformity for current revisions. Measurement CAT II 300V, CAT I 1000V. Pollution Degree 2 |           |       |
| EMC:                                                           | IEC 61326, EN 61326, CISPR 11, ICES-001, AS/NZS 2064.1, refer to Declaration of Conformity for current revisions.                                                                   |           |       |
| Vibration & shock:                                             | MIL-T-28800E, Type III, Class 5 (Sine only)                                                                                                                                         |           |       |
| LXI compliance:                                                | LXI Class C, ver. 1.0                                                                                                                                                               |           |       |
| Warranty:                                                      | 3 year standard                                                                                                                                                                     |           |       |

**myKeysight****myKeysight**[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.

**Three-Year Warranty**[www.keysight.com/find/ThreeYearWarranty](http://www.keysight.com/find/ThreeYearWarranty)

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.

**Keysight Assurance Plans**[www.keysight.com/find/AssurancePlans](http://www.keysight.com/find/AssurancePlans)

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.

[www.keysight.com/go/quality](http://www.keysight.com/go/quality)

Keysight Technologies, Inc.

DEKRA Certified ISO 9001:2008

Quality Management System

**Keysight Infoline****Keysight Infoline**[www.keysight.com/find/service](http://www.keysight.com/find/service)

Keysight's insight to best in class information management. Free access to your Keysight equipment company reports and e-library.

**Keysight Channel Partners**[www.keysight.com/find/channelpartners](http://www.keysight.com/find/channelpartners)

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

[www.keysight.com/find/L4411A](http://www.keysight.com/find/L4411A)[www.keysight.com/find/dmm](http://www.keysight.com/find/dmm)

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

**Americas**

|               |                  |
|---------------|------------------|
| Canada        | (877) 894 4414   |
| Brazil        | 55 11 3351 7010  |
| Mexico        | 001 800 254 2440 |
| United States | (800) 829 4444   |

**Asia Pacific**

|                    |                |
|--------------------|----------------|
| Australia          | 1 800 629 485  |
| China              | 800 810 0189   |
| Hong Kong          | 800 938 693    |
| India              | 1 800 11 2626  |
| Japan              | 0120 (421) 345 |
| Korea              | 080 769 0800   |
| Malaysia           | 1 800 888 848  |
| Singapore          | 1 800 375 8100 |
| Taiwan             | 0800 047 866   |
| Other AP Countries | (65) 6375 8100 |

**Europe & Middle East**

|             |                |
|-------------|----------------|
| Austria     | 0800 001122    |
| Belgium     | 0800 58580     |
| Finland     | 0800 523252    |
| France      | 0805 980333    |
| Germany     | 0800 6270999   |
| Ireland     | 1800 832700    |
| Israel      | 1 809 343051   |
| Italy       | 800 599100     |
| Luxembourg  | +32 800 58580  |
| Netherlands | 0800 0233200   |
| Russia      | 8800 5009286   |
| Spain       | 800 000154     |
| Sweden      | 0200 882255    |
| Switzerland | 0800 805353    |
| Opt. 1 (DE) | Opt. 2 (FR)    |
| Opt. 3 (IT) | United Kingdom |
|             | 0800 0260637   |

For other unlisted countries:

[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

(BP-04-23-15)

This information is subject to change without notice.

© Keysight Technologies, 2011 - 2015

Published in USA, May 28, 2015

5989-6303EN

[www.keysight.com](http://www.keysight.com)