


Keysight E7515A

UXM Wireless Test Set



Data Sheet

Make a Clear Call

The team looks to you: will a new chipset or UE pass the crucial tests? Clarity comes from accumulated insights – insights enabled by the Keysight Technologies, Inc. UXM wireless test set. The UXM is a highly integrated signaling test set created for functional and RF design validation in the 4G era and beyond. It provides the capabilities you need to test the newest designs, delivering LTE-Advanced data rates up to 600 Mbps now and handling more complex requirements later. When the team counts on you, count on the UXM to help you assess design readiness with greater confidence and make a clear call.

Definitions and Conditions

The specifications in this document apply to single TRX instruments with serial number MY5520xxxx/TH5520xxxx and dual TRX instruments with serial number MY5521xxxx/TH5521xxxx.

The test set will meet its specifications when

- The test set is within its calibration cycle
- The test set has been stored at an ambient temperature within the allowed operating range for at least two hours before being turned on; if it had previously been stored at a temperature range inside the allowed storage range, but outside the allowed operating range
- The test set has been turned on for at least 30 minutes

Specification

Specifications describe the performance parameters covered by the product warranty and are valid from 20 to 35 °C unless otherwise noted.

Typical

Typical describes additional product performance information that is not covered by the product warranty. It is performance beyond specifications that 95 percent of the units exhibit with a 95 percent confidence level. This data, shown in italics, does not include measurement uncertainty, and is valid only at room temperature (23 °C).

Nominal

Nominal values indicate expected performance, or describe product performance that is useful in the application of the product, but are not covered by the product warranty.

Vector Signal Analyzer Performance

Frequency and time specification		
Operating frequency range		
E7515A-504		300 MHz to 3.8 GHz
E7515A-506		300 MHz to 6.0 GHz
Frequency setting resolution		100 kHz
Frequency accuracy		See Timebase specifications
VSWR all RF inputs		
300 MHz to 2.0 GHz		1.4 nominal
> 2.0 to 5.0 GHz		1.5 nominal
> 5.0 to 6.0 GHz		1.8 nominal
Amplitude and range specifications		
CW level accuracy		
-60 to +30 dBm for Rx1, Rx2;		
-53 to +30 dBm for TxRx1, TxRx2		
300 MHz to 3.5 GHz		± 0.45 dB typical
> 3.5 to 6.0 GHz		± 0.45 dB typical
-53 to +3.5 dBm		
300 MHz to 3.5 GHz		± 1.0 dB
> 3.5 to 6 GHz		± 1.1 dB
Level flatness		± 0.3 dB typical over 100 MHz bandwidth
Noise floor		
For combined Tx and Rx		< -140 dBm/Hz nominal
For separate Tx and Rx		< -150 dBm/Hz nominal
Maximum CW input level at connectors		
TxRx1 and TxRx2		+33 dBm

Vector Signal Generator Performance

Frequency and time specification		
Operating frequency range		
E7515A-504		300 MHz to 3.8 GHz
E7515A-506		300 MHz to 6.0 GHz
Frequency setting resolution		100 kHz
Frequency accuracy		See Timebase specifications
VSWR all RF inputs		
300 MHz to 2.0 GHz		1.4 nominal
> 2.0 to 5.0 GHz		1.5 nominal
> 5.0 to 6.0 GHz		1.8 nominal
Amplitude and range specifications		
CW output power range		
TxRx1, TxRx2		-110 to -7 dBm nominal (<i>-110 to -10 dBm for typical and warranted</i>)
Tx1, Tx2		-110 to +5 dBm nominal (<i>-110 to 0 dBm for typical and warranted</i>)
CW output level accuracy		
TxRx1, TxRx2 and Tx1, Tx2		
300 MHz to 3.5 GHz		$\pm 1.0, \pm 0.45$ dB typical
> 3.5 to 6.0 GHz		$\pm 1.0, \pm 0.45$ dB typical
Output level setting resolution		0.1 dB
Output level settling time		± 1.0 dB within 25 μ s nominal
Output flatness		± 0.3 dB typical over 100 MHz bandwidth
Harmonics		
Attenuation of 2 nd harmonic TxRx1, TxRx2		
300 MHz to 4.0 GHz, power < -10 dBm		> 30 dB nominal
> 4.0 to 6.0 GHz, power < -10 dBm		> 45 dB nominal
Attenuation of 2 nd harmonic Tx1, Tx2		
300 MHz to 4.0 GHz, power < 0 dBm		> 30 dB nominal
> 4.0 to 6.0 GHz, power < 0 dBm		> 45 dB nominal
Attenuation of 3 rd harmonic TxRx1, TxRx2		
300 MHz to 3.0 GHz, power < -10 dBm		> 40 dB nominal
> 3.0 to 6.0 GHz, power < -10 dBm		> 55 dB nominal
Attenuation of 3 rd harmonic Tx1, Tx2		
300 MHz to 3.0 GHz, power < 0 dBm		> 40 dB nominal
> 3.0 to 6.0 GHz, power < 0 dBm		> 55 dB nominal
Attenuation of non-harmonics TxRx1, TxRx2		
300 MHz to 6.0 GHz, -10 dBm > power > -40 dBm		> 40 dB nominal
Attenuation of non-harmonics Tx1, Tx2		
300 MHz to 6.0 GHz, -10 dBm > power > -40 dBm		> 40 dB nominal
Phase noise		-90 dB at 10 kHz offset nominal
Maximum reverse power		
TxRx1, TxRx2		< +33 dBm
Tx1, Tx2		< +30 dBm

Instrument Specifications

Input power requirements	
Voltage and frequency	100/120/220/240 VAC, 50/60 Hz, nominal
Power consumption (instrument with 2 TRXs)	1100 W max
Additional specifications	
Dimensions (H x W x L)	
Without feet and handles	305 mm x 435 mm x 445 mm
With feet and handles	321 mm x 435 mm x 504 mm
Weight	
One TRX	33 kg
Two TRXs	36 kg
Operating temperature	5 to 45 °C, 30 g/m ³ absolute humidity, 5 to 85% non-condensing relative humidity
Storage temperature	-40 to +65 °C, 50 g/m ³ absolute humidity, 5 to 85% non-condensing relative humidity
Altitude	Up to 2000 m
Radiated leakage due to RF generator	< 2.5 μ V induced in a resonant dipole antenna one inch from any surface except the underside and rear panel set RF generator output frequency and output level of -40 dBm typical
EMC	<p>Complies with European EMC Directive 2004/108/EC</p> <ul style="list-style-type: none"> – IEC/EN 61326-1 – CISPR Pub 11 Group 1, class A – AS/NZS CISPR 11 – ICES/NMB-001 – This ISM device complies with Canadian ICES-001. Cet appareil ISM est conforme a la norme NMB-001 du Canada. – South Korean Class A EMC declaration: This equipment is Class A suitable for professional use and is for use in electromagnetic environments outside of the home. A급 기기 (업무용 방송통신기 자재) 이 기기는 업무용(A급) 전자파 적합기기로서 판매자 또는 사용자는 이 점을 주의하시기 바라며, 가정외의 지역에서 사용하는 것을 목적으로 합니다.
Mechanical resistance	EN60068-2-6, EN60068-2-27, EN60068-2-64
Safety	<p>Complies with European Low Voltage Directive 2006/95/EC</p> <ul style="list-style-type: none"> – IEC/EN 61010-1, 3rd edition – Canada: CAN/CSA C22.2 No. 61010-1012 – USA: UL std no. 61010-1, 3rd Edition – Acoustic statement (European Machinery Directive 2002/42/EC, 1.7.4.2u) Acoustic noise emission, LpA <70 dB, Operator position, Normal operation mode, Per ISO 7779
RF connections	
Tx1, Tx2	N-type female, 50 Ω nominal
TxRx1, TxRx2	N-type female, 50 Ω nominal
Other connectors and interfaces	
Display/Manual user interface	15.4 in (391 mm) active matrix, color, 1280 x 800 pixel resolution TFT-LCD flat panel display with touch panel controls; single-touch capacitive touch-screen; HDMI port
USB ports	
Front panel	2 USB 2.0 ports
Rear	2 USB 2.0 ports
LAN (local area network) ports	<p>One external, 1 Gbps, LAN port rear panel</p> <p>One external, 1 Gbps, LAN port front panel</p>

Instrument Specifications (continued)

Digital data acquisition	
General memory budgets and considerations	
RCB available memory	512 MB
Memory allocation for digital acquisition	256 MB
Basic acquisitions	
IQ data acquisition channels	2 (one per BS Rx antenna)
Samples rates	30.72 MSa/s, 122.88 MSa/s
Maximum sample storage	32 MSa per BS Rx antenna
Fixed size buffers per channel and allocation	
Single or dual channel (RF Carrier)	30.72 MHz: 1092 ms
Single or dual channel (RF Input)	122.88 MHz: 273 ms
Maximum digitalized data size	128 MB per channel
Trigger control	Immediate, event-based Ethernet
Source selection	
RF Input (1 & 2)	100 MHz bandwidth (122.88 MSa/s)
RF Carrier (1 & 2)	20 MHz bandwidth (30.72 MSa/s)
Channel emulation	
Antenna configuration	1x1, 1x2, 2x2, 4x2
3GPP LTE Rel 8 for RF fading profiles	Bypass EPA 5, custom Max Doppler frequency EVA 5, 70, 200, custom Max Doppler frequency ETU 70, 200, 300, custom Max Doppler frequency HST CQI
Gaussian noise generator	
Independent channels	2
Antenna output	No channel Channel 1 Channel 2 Channel 1 and 2
Power spectral density	
Combined Tx and Rx	-189 to -81 dBm/Hz
Separate Tx and Rx	-179 to -71 dBm/Hz
Digital frequency offset	-49.6 to 49.6 MHz
Bandwidth selection	
LTE	1.08, 2.7, 4.5, 9.0, 13.5, 18.0 MHz
Continuous wave generation	
Independent channels	2
Antenna output	No channel Channel 1 Channel 2 Channel 1 and 2
Digital frequency offset	-50 to 50 MHz

Instrument Specifications (continued)

Time base	
Standard frequency reference	
Maximum frequency drift	±0.7 ppm/year
Short term stability	±0.005 ppm
Warm-up time	1 minute to be ±0.1 ppm at 25 °C
External clock time reference	
Connector type	SMA connector SYNC IN, rear panel
Frequency	
Sine wave	10 MHz
Square wave (greater than 40% ON duty cycle)	10 MHz
Input voltage range	0.4 to 2 Vpp
Impedance	50 Ω nominal
Format alignment trigger	
External connector	SMA Channel 0
Trigger duration configurable according format LTE	Where samples resolution = $(1/30.72) \times 10^{-6}$ 0 to 30719 samples
Trigger offset delay	In terms of 1/6 of the period of the sample
Trigger period configurable according format LTE	1 to 10240 packets
Generic trigger	
External connector	SMA Channel 1, 2, 3 (Input, Output)
Arm channel for receiving trigger	Only input channels
External trigger generation	Only output channels
Warranty and calibration	
Standard warranty	Three years
Recommended calibration cycle	One year

LTE Measurements

Modulation and channels	
Signal structure	FDD and TDD (with appropriate licenses)
Signal bandwidth	1.4, 3, 5, 10, 15, 20 MHz
LTE signal generation	
Error vector magnitude (EVM)	
20 MHz LTE PDSCH signal with full allocation (100 RBs)	
modulation = 64QAM; power = -20 dBm	
300 MHz to 3.5 GHz	< 2% RMS nominal
> 3.5 to 6 GHz	< 2.25% RMS nominal
LTE power measurements	
Level range (BW 20 MHz, OFDM, 64QAM)	-45 to +30 dBm, RMS
LTE channel power accuracy	±0.65 dB nominal
LTE adjacent channel power	
Dynamic range	
E-UTRA	> 45 dB nominal
UTRA	> 45 dB nominal
Residual EVM (5, 10, 15, 20 MHz bandwidths)	< 2% RMS typical at -20 dBm input power



myKeysight



3 YEAR WARRANTY



5 YEAR ASSURANCE WARRANTY



DEKRA Certified ISO 9001:2008

myKeysight

www.keysight.com/find/mykeysight

A personalized view into the information most relevant to you.

Three-Year Warranty

www.keysight.com/find/ThreeYearWarranty

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.

Keysight Assurance Plans

www.keysight.com/find/AssurancePlans

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.

www.keysight.com/go/quality

Keysight Technologies, Inc.

DEKRA Certified ISO 9001:2008

Quality Management System

www.keysight.com/find/uxm

www.keysight.com/find/e7515a

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

Americas	
Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444
Asia Pacific	
Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 11 2626
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

Europe & Middle East	
Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:
www.keysight.com/find/contactus
 (BP-04-23-15)