

SMA Female Connector Compression Attachment 2 Hole Flange Stub Terminal, .481 inch Hole Spacing



TECHNICAL DATA SHEET

PE44340

SMA Female Connector Compression Attachment 2 Hole Flange Stub Terminal, .481 inch Hole Spacing

Configuration

Connector

Connector Interface Type

Cable Attachment Method (Shield/Contact)

Body Style

Mount Method

SMA Female

Stub

Compression

Straight

2 Hole Flange

Electrical Specifications

Frequency Range, GHz DC to 27 Impedance, Ohms 50 Maximum VSWR 1.2:1

Mechanical Specifications

Size

 Length, in [mm]
 0.562 [14.27]

 Width/Dia., in [mm]
 0.223 [6]

 Height, in [mm]
 0.625 [15.88]

 Weight, lbs [g]
 0.005 [2.27]

Connector

Type SMA Female
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification MIL-G-45204, Type II, Class 1
Body Material and Plating Stainless Steel, Gold
Body Plating Specification MIL-G-45204
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-standard-stub-terminal-connector-pe44340-p.aspx

SMA Female Connector Compression Attachment 2 Hole Flange Stub Terminal, .481 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44340 CAD Drawing

SMA Female Connector Compression Attachment 2 Hole Flange Stub Terminal, .481 inch Hole Spacing

