



Model: SR-3010-4S

Description:..... SP4T, Absorptive, PIN-Switch

Operating Frequency:..... 10 – 3000 MHz

Insertion Loss:

10 – 1000 MHz	1000 - 3000 MHz
1.5 dB Max	2.2 dB Max

Isolation:

10 – 1000 MHz	1000 - 3000 MHz
65 dB Min	60 dB Min

VSWR (RF Path “ON” or “OFF”): 1.5:1 Max
Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 350 ns Max
On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF):..... 900 ns Max
Operating Power:..... CW&AVG..... +27dBm (+30dbm @ COM Port)
..... Peak: 5W @ 5μS PW Max
Control Input Characteristics: TTL / Unit-Load / Floating-High
Control Logic:..... 4-Controls, Logic “0” = RF Path “ON”
Power Supplies:..... +5(±0.25)V @ 150mA Max
..... -12(±0.5)V @ 80mA Max
Connectors (RF): SMA (f), Removable
Connectors (Supplies/Controls) Solder Pins
Impedance: 50 Ohms Nominal
Quality:..... Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}
Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)
Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)
Vibration: MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)
Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)
Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

A1 [+5(±0.25)V / -5(±0.25)V]
A2 [+5(±0.25)V / -15(±0.5)V]
A3 [+12(±0.5)V / -12(±0.5)V]
A4 [+15(±0.5)V / -15(±0.5)V]

■ **RF Connectors**

B1 [J1 – J4 Ports with SMA(M)]
B2 [All SMA (M)]
B3 [COM Port with SMA(M)]

■ **Control Function**

F1 [Inverse Logic, (“1” = Path “ON”)]
F2 [2-BCD Control + Enable]



Outline

