Termination BNC


BTRM-75+

DC to 1000 MHz 75Ω

Maximum Ratings

Operating Temperature -55°C to 100°C Storage Temperature -55°C to 100°C Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch)

| wt | D | В | Α |
|-------|-------|-------|-------|
| grams | .75 | .58 | 1.46 |
| 21.5 | 19.05 | 14.73 | 37.08 |

Features

- return loss, 30 dB typ. up to 500 MHz
- rugged construction

CASE STYLE: LL85

| Co | nnectors | Model | Price | Qty. |
|----|----------|----------|------------|-------|
| BN | C-Male | BTRM-75+ | \$9.95 ea. | (1-9) |

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Applications

- test set-up
- · cellular communications

Electrical Specifications

| FREQUENCY (MHz) | IMPEDANCE (OHMS) | RETURN LOSS (dB) MIN. | POWER RATING* (W) |
|--------------------|---------------------|--------------------------|-------------------------|
| | | DC5 DC-1 GHz GHz | |
| DC-1000 | 75 | 30 20 | 0.5 |

^{*} At 70°C, derate linearly at 5mW/°C to 350mW at 100°C.

Typical Performance Data



A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits website at www.minicircuits.com/WCLStore/terms.jsp



