

50 Ohm 2 Watts Precision Brass N Male RF Load With Chain Up To 18 GHz



TECHNICAL DATA SHEET

PE6075

50 Ohm 2 Watts Precision Brass N Male RF Load With Chain Up To 18 GHz

Configuration

RF Load Design Precision
Connector N Male
Connector Specification MIL-STD-348
Connection Method Standard
Body Style Straight

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

Maximum Input Power, Watts

DC to 18

1.3:1

2

Mechanical Specifications

Temperature

Size

 Length, in [mm]
 0.96 [24.38]

 Width/Dia., in [mm]
 0.8 [20.32]

Connector

Type N Male

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/2-watts-n-male-rf-load-up-to-18-ghz-precision-pe6075-p.aspx

50 Ohm 2 Watts Precision Brass N Male RF Load With Chain Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE6075 CAD Drawing50 Ohm 2 Watts Precision Brass N Male RF Load With Chain Up To 18 GHz

