


**TNC Male Connector Solder Attachment 4 Hole
Flange Pin Terminal, .531 inch Hole Spacing**
TECHNICAL DATA SHEET
PE44654
TNC Male Connector Solder Attachment 4 Hole Flange Pin Terminal, .531 inch Hole Spacing
Configuration

Connector	TNC Male
Connector Specification	MIL-C-39012
Connector Interface Type	Pin
Cable Attachment Method (Shield/Contact)	Solder
Body Style	Straight
Mount Method	4 Hole Flange

Electrical Specifications

Frequency Range, GHz	DC to 11
Impedance, Ohms	50
Maximum Operating Voltage, Volts	500

Mechanical Specifications

Temperature	
Operating Range, deg C	-65 to +165
Size	
Length, in [mm]	1.55 [39.37]
Width/Dia., in [mm]	0.75 [19.05]
Height, in [mm]	0.75 [19.05]
Weight, lbs [g]	0.055 [24.95]

Connector

Type	TNC Male
Contact Material and Plating	Gold
Contact Plating Specification	MIL-G-45204
Coupling Nut Material and Plating	Brass, Nickel
Body Material and Plating	Brass, Nickel
Dielectric Type	Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Connector Solder Attachment 4 Hole Flange Pin Terminal, .531 inch Hole Spacing PE44654](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.





**TNC Male Connector Solder Attachment 4 Hole
Flange Pin Terminal, .531 inch Hole Spacing**

TECHNICAL DATA SHEET

PE44654

Plotted and Other Data

Notes:

Values at 25 °C, sea level

TNC Male Connector Solder Attachment 4 Hole Flange Pin Terminal, .531 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [TNC Male Connector Solder Attachment 4 Hole Flange Pin Terminal, .531 inch Hole Spacing PE44654](http://www.pasternack.com/tnc-male-standard-pin-terminal-connector-pe44654-p.aspx)


URL: <http://www.pasternack.com/tnc-male-standard-pin-terminal-connector-pe44654-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44654 CAD Drawing

TNC Male Connector Solder Attachment 4 Hole Flange
Pin Terminal, .531 inch Hole Spacing



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

PASTERNAK®	DWG TITLE	PE44654	FSCM NO.	53919	CAD FILE	062509	SCALE	N/A	SIZE	A	xxxx
PASTERNAK® Pasternack Enterprises, Inc. P.O. Box 16759 Irvine CA 92623 Phone: (949) 261-1920 Fax: (949) 261-7451 Website: www.pasternack.com E-Mail: sales@pasternack.com											