

SPECIFICATION SHEET**JFW MODEL 50S-1220****1P2T SELF TERMINATING SOLID STATE RF SWITCH**

JFW Industries, Inc.
Phone: 317-887-1340
sales@jfwindustries.com
www.jfwindustries.com

Frequency Range	20-4300 MHz
Configuration	1P2T Self Terminating
Impedance	50 Ohms nominal
VSWR	1.5:1 maximum
Insertion Loss	1.5 dB maximum 20-1000 MHz 3.0 dB maximum 1000-4300 MHz
Isolation	80 dB minimum 20-1000 MHz 70 dB minimum 1000-2000 MHz 60 dB minimum 2000-4000 MHz 55 dB minimum 4000-4300 MHz
Switching Speed	10 microseconds
RF Input Power	+20 dBm average 20-100 MHz +30 dBm average 100-4300 MHz
Control Logic (2 Lines)	TTL High for ON [i.e. C1 High for J1-J3 (common)] TTL Low for OFF and internally terminated in 50 Ohms
DC Supply	+5 Vdc @ 50 mA +24 Vdc @ 50 mA
DC Connector	DE-9P
RF Connector	SMA female
Operating Temperature Range	0°C to +70°C
Storage Temperature Range	-55°C to +90°C
Physical Size	See outline drawing 092-3725-24

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	07/25/2001						
9999	02/06/2003	A	TRS 04/08/2003				
18933	07/30/2010	B	TRS 07/30/2010				