

Rev: November 2014



Absolute maximum ratings

Parameter	Min	Max
V_{ds}	-0.5 V	3 V
I_{ds}		100 mA
V_{gs}	-20 V	+20 V
RF Input drive level		-10 dBm

Product features

- RF bandwidth: 7-10 GHz
- Noise: 4.7K typical
- Gain: 35dB
- DC-power: $V_d=0.90V$ @ 20mA
- One gate and one drain supply only
- RF-connectors: female SMA
- DC-connector: 9-pin female Nano-D

Typical RF Characteristics

Parameter	Test Condition	Value	Unit
Gain	7-10 GHz	35	dB
Noise	7-10 GHz	4.7	K
IRL	7-10 GHz	20	dB
ORL	7-10 GHz	20	dB
P_{1dB}	8.5 GHz	0	dBm
OIP3	8.5 GHz	10	dBm

Product description


LNF-LNC7_10A is an ultra-low noise cryogenic amplifier operating in the 7-10 GHz frequency range. The LNA is packaged in a coaxial module using industry standard SMA and Nano-D connectors. The lightweight gold plated aluminum module measures 22.00*19.60*7.80 mm excluding the connectors. MMIC technology ensures reliable and repeatable unit-to-unit result.

Typical DC Characteristics

Parameter	Value	Unit
V_{ds}	0.90	V
I_{ds}	20	mA
V_{gs}	-4.2 V	V
I_{gs}	-400	μA
P_{dc}	18	mW

Rev: November 2014


Measured typical data $T_{amb}=5$ K




Rev: November 2014

Measured typical data @ $T_{amb}=296K$

Gain and Noise







S11 and S22



Rev: November 2014

Drawings



Dimensions are in millimeters