

High Reliability Mixer

Level 7 (LO Power +7 dBm) 5 to 600 MHz

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA

Permanent damage may occur if any of these limits are exceeded


Pin Connections

LO	4
RF	1
IF	2
GROUND	3
CASE GROUND	3

Outline Drawing



PCB Land Pattern




Suggested Layout,
Tolerance to be within $\pm .002$

Outline Dimensions ($\frac{\text{inch}}$)

A	B	C	D	E	F	G
.50	.48	.255	.240	.23	.21	.06
12.70	12.19	6.48	6.10	5.84	5.33	1.52
H	J	K	L	M	N	wt
.100	.09	.16	.020	.09	.005	grams
2.54	2.29	4.06	0.51	2.29	0.13	1.9

Demo Board MCL PIN: TB-201
Suggested PCB Layout (PL-081)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS $0.030" \pm 0.002"$; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.

2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- hermetically sealed ceramic quad
- low conversion loss, 5.9 dB typ.
- excellent isolation L-R, 50 dB typ; L-I, 48 dB typ.
- rugged welded construction
- shielded metal case

Applications

- VHF/UHF
- FM radio
- defense & federal communications

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)						IP3 at center band (dBm)
LO/RF	IF	Mid-Band			Total Range Max.	L		M		U		L		M		U		
		$\overline{X}$	σ	Max.		Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	
		f_L - f_U																
5-600	DC-600	5.9	0.2	7.0	8.0	60	45	50	32	42	26	60	43	48	34	40	25	16


1 dB COMP.: +1 dBm typ.

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]
m = mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm
4.00	34.00	6.06	66.56	61.24	1.36	2.64
6.00	36.00	5.95	66.02	61.15	1.25	2.58
10.00	40.00	5.89	65.37	60.45	1.17	2.70
32.00	62.00	5.92	61.99	57.62	1.11	2.65
40.50	70.50	5.94	61.46	57.67	1.11	2.72
49.00	79.00	5.93	60.24	56.26	1.11	2.56
66.00	96.00	5.94	58.07	54.36	1.11	2.47
74.50	104.50	5.95	58.24	54.77	1.11	2.64
83.00	113.00	5.95	57.74	54.71	1.11	2.65
91.50	121.50	5.95	57.54	54.68	1.11	2.59
100.00	130.00	5.95	56.70	53.58	1.11	2.68
160.00	190.00	5.95	53.29	50.36	1.13	2.61
220.00	250.00	5.96	51.73	49.52	1.15	2.79
250.00	280.00	5.95	50.55	48.71	1.15	2.55
310.00	340.00	5.96	49.80	47.68	1.17	2.74
340.00	370.00	5.93	49.37	46.42	1.20	2.48
400.00	430.00	5.97	46.91	43.69	1.18	2.76
442.50	472.50	5.99	46.17	43.81	1.20	2.74
527.50	557.50	6.08	46.85	41.81	1.27	2.74
600.00	630.00	6.25	45.82	42.54	1.29	2.47

Electrical Schematic



CASE STYLE: NNN150
PRICE: \$8.60 ea. QTY. (10)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

REV. OR
M109914
TUF-R1SM+
ED-12916/1
WL/TD/AM
130502
Page 1 of 2

