


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 6–14 GHz
Insertion Loss: 1.4dB Max.
Isolation: 17dB Min.
VSWR Input/Output: 1.80:1/1.80:1 Max.
Amplitude Balance: 0.4dB Max.
Power: 10W (Load vswr@1.2)

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET:	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .01 \pm .005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: 3-WAY POWER DIVIDER			
		PART NO. PS3-4/NF			
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		CAGE CODE: OD2L5	SIZE: A	REV: N/A	DWG NO. 80105
THIRD ANGLE PROJECTION 	DO NOT SCALE THE DRAWING				
DRAWN: Paiboon Luekhamhan	DATE: 10-21-1997				
APPROVED: T. Nguyen	DATE: 10-21-1997				