



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## Product Specifications Approval Sheet

Product Description: SAW Filter 1128 MHz SMD 3.0X3.0 mm

TST Part No.: TA1413A

Customer Part No.: \_\_\_\_\_

Customer signature required

Company: \_\_\_\_\_

Division: \_\_\_\_\_

Approved by : \_\_\_\_\_

Date: \_\_\_\_\_

Checked by: \_\_\_\_\_ Bob Chau 

Approved by: \_\_\_\_\_ Francis Chen 

Date: \_\_\_\_\_ 10, 4, 2011

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [ttsales@mail.taisaw.com](mailto:ttsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## SAW Filter 1128 MHz

MODEL NO.:TA1413A

REV. NO.:1

### A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C

RoHS Compliant  
Lead free  
Lead-free soldering

Electrostatic Sensitive Device (ESD)


### B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (single ended) :  $Z_s = 50 \Omega$

Terminating load impedance (single ended) :  $Z_L = 50 \Omega$

| Item                                           | Unit   | Min. | Typ. | Max. | Note |
|------------------------------------------------|--------|------|------|------|------|
| <b>Center Frequency</b> <b>F<sub>c</sub></b>   | MHz    | -    | 1128 | -    | -    |
| <b>Insertion Loss</b> (1111 ~ 1145 MHz)        | dB     | -    | 2.85 | 4    | -    |
| <b>Amplitude Variation</b> (1111 ~ 1145 MHz)   | dB     | -    | 0.8  | 2    | -    |
| <b>Amplitude Variation over 3 MHz</b>          | dB     | -    | 0.4  | 1    | -    |
| <b>VSWR</b> (1111 ~ 1145 MHz)                  |        | -    | 2.1  | 2.4  | -    |
| <b>Group Delay Variation over 3 MHz</b>        | ns     | -    | 5    | 20   | -    |
| <b>Attenuation</b> (reference level from 0 dB) |        |      |      |      |      |
| DC~1090 MHz                                    | dB     | 30   | 47   | -    | -    |
| 1163~1190 MHz                                  | dB     | 6    | 19   | -    | -    |
| 1190~2000 MHz                                  | dB     | 30   | 44   | -    | -    |
| <b>Temperature Coefficient of Frequency</b>    | ppm/°C | -    | -36  | -    | -    |


### C.OUTLINE DRAWING:




△ : Year Code (2009->9, 2010->0,..., 2018->8)

□ : Date Code (W01->A,W02->B,...W27->a,...,W52->z)



### D. MEASUREMENT CIRCUIT:



E. PCB Footprint:




## F. Frequency Characteristics :




Reflection Functions :

S11




S22




## G. PACKING:

### 1. REEL DIMENSION



### 2. TAPE DIMENSION



## H. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time : 2 times.

