


SPECIFICATIONS

Frequency Range: 8–12 GHz
 Insertion Loss: 2.9dB Max.
 Isolation: 14dB Min.
 Amplitude Balance: ±2dB Max.
 VSWR: 1.90:1 Max.
 Input Power: 10 Watts

MATERIAL:		 MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM	SCALE:	N/A
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°			SHEET:	N/A
DRAWING TITLE:		12-WAY POWER DIVIDER		
PART NO.:		PS12-17		
DRAWN:	DATE:	PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	CAGE CODE:	SIZE:
APPROVED:	DATE:		OD2L5	C
THIRD ANGLE PROJECTION 		DWG NO.:	DO NOT SCALE THE DRAWING	
Paiboon Luekhamhan T. Nguyen		04-08-2009	84362	