

TERMINATIONS SMA

DC - 12.4 GHz
40 WATTS

api 
technologies corp.
> INMET

MODELS: 3114SM, 3114SF

SPECIFICATIONS:

Electrical:

Frequency Range _____ DC — 12.4 GHz

VSWR:

DC — 1 GHz _____ 1.10:1 Max.

1 — 4 GHz _____ 1.20:1 Max.

4 — 8 GHz _____ 1.25:1 Max.

8 — 12.4 GHz _____ 1.35:1 Max.

Impedance _____ 50 Ohms

Input Power _____ 40 Watts Avg. @ +25°C

(Derated Linearly to 8 Watts @ +125°C)

Peak Power _____ 4 kW Max. @ +25°C

(5uSec Pulse, .05% Duty Cycle)

Operating Temp Range _____ -55°C to +125°C

Mechanical:

SMA Connectors _____ Passivated Stainless Steel


Mates with MIL-STD-348

Housing _____ Anodized Aluminum

Conductors _____ Gold Plated Beryllium Copper


Model Number: **3114SM**

SMA Male Connector



Model Number: **3114SF**

SMA Female Connector



Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.

Design specifications are subject to change without notice.

Contact factory for technical specifications before purchasing or use.

3114S; REV A

300 Dino Drive • Ann Arbor, MI 48103-9457 U.S.A. • 888-244-6638 or 734-426-5553 • FAX 734-426-5557 • inmet.apitech.com