

## SMA Male to Reverse Polarity TNC Female Adapter



### TECHNICAL DATA SHEET

PE9600

#### **SMA Male to Reverse Polarity TNC Female Adapter**

Configuration

Connector 1 SMA Male Impedance 1 50 Ohms

Connector 2 TNC Female Reverse Polarity

Impedance 250 OhmsAdapter DesignStandardBody StyleStraight

#### **Mechanical Specifications**

Size

Length, in [mm] 1.157 [29.39] Width/Dia., in [mm] 0.5 [12.7]

Connector 1

Type SMA Male Inner Conductor Material and Plating Gold Coupling Nut Material and Plating Brass, Nickel Hex Size, in. 5/16

Torque, in-lbs [Nm] 5 [0.57]
Body Material and Plating Brass, Nickel Dielectric Type PTFE

Connector 2

Type TNC Female Reverse Polarity

Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-male-tnc-female-straight-adapter-pe9600-p.aspx

SMA Male to Reverse Polarity TNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

# PE9600 CAD Drawing

SMA Male to Reverse Polarity TNC Female Adapter

