

RF AMPLIFIER

MODEL QBH-2818

Available as: QBH-2818 (400-22678-0001)

Features

- High Output Power: +30 dBm Typical
- High Third Order Intercept: +42 dBm Typical

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = +25 °C
Frequency	.35 - 400 MHz	.35 - 400 MHz
Gain (dB) (f=50 MHz)	18.5	17.75 Min.
Power @ 1 dB Comp. (f=200 MHz) (dBm)	30	29 Min.
Reverse Isolation (dB)	-23	-21 Max.
VSWR In Out	1.75:1 1.75:1	2.0:1 Max. 2.0:1 Max.
Noise Figure (dB) (f=200 MHz)	5.0	6.0 Max.
Power Vdc mA	+24 245	+24 260 Max.

Notes:


1. Maximum operating temperature is defined as that temperature which, if exceeded for extended periods, could result in premature unit failure. This data is provided for user reliability information. This may or may not represent the maximum temperature for electrical parameter specifications.
2. Specifications are guaranteed when tested in a 50 Ohm system. Specifications indicated as typical are not guaranteed.
3. Care should always be taken to effectively ground the case of each unit.

Typical Intermodulation Performance at 25 ° C


Second Order Two Tone Intercept Point +68 dBm (Typ.)
Third Order Two Tone Intercept Point +42 dBm (Typ.)

Absolute Maximum Ratings

Ambient Operating Temperature -20°C to +100 °C
Storage Temperature -40°C to +100 °C
Case Temperature +100 °C
DC Voltage +28 Volts
Continuous RF Input Power +14 dBm



Typical Performance Data



Legend — + 25 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev.
11/7/07

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001