


FAT-TM5TF5T3G2W6

3GHz TNC Plug To TNC Jack Fixed Attenuator



Nominal impedance: 50Ω $\pm$ 0.25Ω over operating temperature range.  
 Operating temperature range: -50 degrees Celcius to +80 degrees Celcius.  
 VSWR deviation:  $\pm$ 0.1% over operating temperature range.  
 Power rating: 2W over operating temperature range.  
 Power Rating (Peak): 100W for 25 Microseconds.  
 Power Coefficient: 0.001dB/W (change in attenuation with increase in power).  
 Temperature Coefficient: 0.001dB/Deg. C max., 0.0003dB/Deg. C typ.

| Attenuation | VSWR       |             | Attenuation deviation (+/-dB) |             |
|-------------|------------|-------------|-------------------------------|-------------|
|             | DC-2GHz    | 2-3GHz      | DC-2GHz                       | 2-3GHz      |
| 6dB         | $\leq$ 1.1 | $\leq$ 1.25 | $\pm$ 0.2dB                   | $\pm$ 0.3dB |

| Parts         | Material        | Plating (Micro-inch)                     |
|---------------|-----------------|------------------------------------------|
| Insulator     | Teflon          |                                          |
| Contact Pin   | Phosphor Bronze | Gold 10 Over Nickel 50 Over Copper 50    |
| Body          | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Retainer Ring | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |
| Gasket        | Silicon         |                                          |
| Coupling Nut  | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50 |

Weight: 34.56 g

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.