


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS:

Frequency Range: 5–11GHz
 Isolation: 15dB Min.
 Insertion loss: 0.80dB Max.
 VSWR: 1.40:1 Max.
 Operating Temperature: –10°C to +60°C
 Average Power: 1 Watt
 R.O.H.S. Compliant

MATERIAL: 		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWING TITLE: COAXIAL ISOLATOR		PART NO. IS-137		
DRAWN: Paiboon Luekhamhan	DATE: 03-22-2011	CAGE CODE: 0D2L5	SIZE: N/A REV: N/A DO NOT SCALE THE DRAWING	DWG NO. 85588
APPROVED: T. Nguyen		DATE: 03-22-2011		