

Bulkhead Isolated Ground TNC Female to TNC Female Adapter



TECHNICAL DATA SHEET

PE9287

Bulkhead Isolated Ground TNC Female to TNC Female Adapter

Configuration

Connector 1 **TNC Female** Connector 2 **TNC Female** Adapter Design Standard Body Style Straight Mount Method Bulkhead

Isolated Ground / Hermetic Isolated Ground

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Temperature

Operating Range, deg C -40 to +85

Length, in [mm] 1.281 [32.54] Width/Dia., in [mm] 0.611 [15.52]

Dielectric Type Delrin

Connector 1

TNC Female Type

Inner Conductor Material and Plating Phosphor Bronze, Gold

Body Material and Plating Brass, Nickel

Connector 2

Type **TNC Female**

Inner Conductor Material and Plating Phosphor Bronze, Gold

Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/tnc-female-tnc-female-straight-adapter-pe9287-p.aspx

Bulkhead Isolated Ground TNC Female to TNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001: 2008 Registered

PE9287 CAD DrawingBulkhead Isolated Ground TNC Female to TNC Female Adapter

