



SMC Jack Connector Solder Attachment 0.042 inch End Launch PCB, .030 inch Diameter

TECHNICAL DATA SHEET

PE44133

SMC Jack Connector Solder Attachment 0.042 inch End Launch PCB, .030 inch Diameter

Configuration

Connector SMC Jack

Connector Interface Type 0.042 inch End Launch

Cable Attachment Method (Shield/Contact)

Solder

Body Style

Straight

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Size

 Length, in [mm]
 0.562 [14.27]

 Width/Dia., in [mm]
 0.375 [9.53]

 Height, in [mm]
 0.312 [7.92]

 Weight, lbs [g]
 0.005 [2.27]

Connector

Type SMC Jack
Contact Material and Plating Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

SMC Jack Connector Solder Attachment 0.042 inch End Launch PCB, .030 inch Diameter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Jack Connector Solder Attachment 0.042 inch End Launch PCB, .030 inch Diameter PE44133

URL: http://www.pasternack.com/smc-jack-standard-0.042-end-launch-connector-pe44133-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



