

SMA Male to SMB Plug Adapter



TECHNICAL DATA SHEET

PE9144

SMA Male to SMB Plug Adapter

Configuration

Connector 1SMA MaleImpedance 150 OhmsConnector 2SMB PlugImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 0.787 [19.99] Width/Dia., in [mm] 0.312 [7.92]

Connector 1

Type SMA Male
Inner Conductor Material and Plating Gold
Coupling Nut Material and Plating Brass, Nickel
Hex Size, in. 5/16
Torque, in-lbs [Nm] 5 [0.57]
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Connector 2

Type SMB Plug
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-male-smb-plug-straight-adapter-pe9144-p.aspx

SMA Male to SMB Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9144 CAD Drawing

SMA Male to SMB Plug Adapter

