



## 75 Ohm BNC Male Connector Crimp/Solder Attachment For 7731A

### TECHNICAL DATA SHEET

PE44628

#### 75 Ohm BNC Male Connector Crimp/Solder Attachment For 7731A

##### Configuration

Connector	BNC Male
Connector Interface Type	7731A
Cable Attachment Method (Shield/Contact)	Crimp/Solder
Body Style	Straight

##### Electrical Specifications

Impedance, Ohms	75
-----------------	----

##### Mechanical Specifications

###### Size

Length, in [mm]	1.17 [29.72]
Width/Dia., in [mm]	0.57 [14.48]
Weight, lbs [g]	0.02 [9.07]

###### Connector

Type	BNC Male
Contact Material and Plating	Gold
Coupling Nut Material and Plating	Brass, Nickel
Body Material and Plating	Brass, Nickel
Dielectric Type	PTFE

##### Compliance Certifications (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant	Yes
----------------	-----

##### Plotted and Other Data

Notes:	Values at 25 °C, sea level
--------	----------------------------

75 Ohm BNC Male Connector Crimp/Solder Attachment For 7731A from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm BNC Male Connector Crimp/Solder Attachment For 7731A PE44628](http://www.pasternack.com/bnc-male-standard-7731a-connector-pe44628-p.aspx)

URL: <http://www.pasternack.com/bnc-male-standard-7731a-connector-pe44628-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE44628 CAD Drawing

75 Ohm BNC Male Connector Crimp/Solder Attachment For 7731A



STRIPPING DIMENSIONS  
CRIMP SIZE REQUIRED  
CONTACT: .080" HEX CRIMP TOOL  
FERRULE: .425" HEX CRIMP TOOL

**PE PASTERNAK®**  
Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE  
**PE44628**  
FSCM NO. 53919

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].  
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

CAD FILE 060508 SCALE N/A SIZE A XXXX