



SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm,
10 Watts, 12V Control with Normally Open, Indicators, TTL

TECHNICAL DATA SHEET

PE71S6136

The PE71S6136 is Single Pole Four Throw Switch that operates from DC to 40 GHz. The switch has a normally open actuator, Indicators and 1M life cycles. The switch has an operating voltage of 12 Volts and has TTL Control.

Features

- SP4T Switch
- DC to 40 GHz Operating Frequency Range
- 1 M Cycles min
- Normally Open Switch
- Indicators
- TTL Control
- Switching Sequence Break Before Make

Applications

- Test & Measurement
- Communications System
- Instrumentation

Electrical Specifications

Frequency Range	DC to 40 GHz
Impedance	50 Ohms
Actuator	Normally Open, Indicators, TTL Logic
Actuating Current	200 mA
Control Voltage	12 Volts
RF Input Power (Max CW)	10 Watts

RF Characteristic

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Frequency Range	DC to 6	6 to 12	12 to 18	18 to 26.5	26.5 to 40	GHz
VSWR, Max	1.3:1	1.4:1	1.5:1	1.7:1	2:1	
Insertion Loss, Max	0.2	0.4	0.5	0.7	0.9	dB
Isolation, Min	70	60	60	55	50	dB

Mechanical Specifications

Connector Type	2.92mm Female
Operating Life	1,000,000
Terminals	Solder Pins
Switching Time (nominal voltage, 25°C)	<15 ms Typ

Environmental Specifications

Temperature	
Operating Range	-35 to +85 deg C
Environment	MIL-DTL-3928
Housing Material and Plating	Aluminum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm, 10 Watts, 12V Control with Normally Open, Indicators, TTL PE71S6136](#)



SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm,
10 Watts, 12V Control with Normally Open, Indicators, TTL

TECHNICAL DATA SHEET

PE71S6136

Compliance Certifications (visit www.Pasternack.com for current document)
Not RoHS Compliant

Plotted and Other Data

Notes:

- Values at +25 °C, sea level
- ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm, 10 Watts, 12V Control with Normally Open, Indicators, TTL PE71S6136](#)





SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm,
10 Watts, 12V Control with Normally Open, Indicators, TTL

TECHNICAL DATA SHEET

PE71S6136

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm, 10 Watts, 12V Control with Normally Open, Indicators, TTL PE71S6136](#)



SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm,
10 Watts, 12V Control with Normally Open, Indicators, TTL

TECHNICAL DATA SHEET

PE71S6136

SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm, 10 Watts, 12V Control with Normally Open, Indicators, TTL from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm, 10 Watts, 12V Control with Normally Open, Indicators, TTL PE71S6136](http://www.pasternack.com/2.92mm-sp4t-electromechanical-relay-switch-40-ghz-normally-open-indicators-ttl-logic-pe71s6136-p.aspx)

URL: <http://www.pasternack.com/2.92mm-sp4t-electromechanical-relay-switch-40-ghz-normally-open-indicators-ttl-logic-pe71s6136-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE71S6136 CAD Drawing

SP4T Electromechanical Relay Switch DC to 40 GHz, 2.92mm,
10 Watts, 12V Control with Normally Open, Indicators, TTL



SCHEMATIC SHOWN IN DE-ENERGIZED POSITION

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE71S6136

FSCM NO. 53919

CAD FILE 022615

SCALE N/A

SIZE A

200

PE PASTERNAK®
THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com