



50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts

TECHNICAL DATA SHEET

PE-T1002

50 Ohm 2 Way 7/16 DIN Power Divider Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts

Pasternack's RF Tapper Power Dividers are designed to be wideband and low loss, with minimal reflections across Mobile Network bands between 380 MHz and 6 GHz. Their Air Dielectric and no Solder Joint designs make them ideal for indoor use, while the rugged construction ensures IP65 or IP67 outdoor performance.

- Optimized at Mobile Network Frequencies between 380 MHz to 6 GHz
- Low Loss and Low PIM, with VSWR as low as 1.15
- · IP65 or IP67 Rated
- Available with High Power N or 7/16 DIN style connectors

Configuration

Input Connector 7/16 DIN Female
Output Connectors 7/16 DIN Female
Frequency Range, GHz 0.7 to 2.7
Number of Output Ports 2
Housing Material and Plating Aluminum, Conversion Coating

Electrical Specifications

Frequency Range, GHz
Impedance, Ohms
50
Maximum Insertion Loss, dB
Maximum Input Power, Watts
700
Maximum Input VSWR
Peak Input Power, KWatts
3

Mechanical Specifications

Size

 Length, in [mm]
 9.71 [246.63]

 Width, in [mm]
 1.5 [38.1]

 Height, in [mm]
 2.34 [59.44]

 Weight, lbs [g]
 2.1 [952.54]

 Humidity
 IP65

Input Connector

Contact Material and Plating Brass, Silver
Connector Material and Plating Brass, Silver
Body Material and Plating Brass, Silver

Output Connectors

Contact Material and Plating Brass, Nickel Connector Material and Plating Brass, Nickel Body Material and Plating Brass, Nickel

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts PE-T1002

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts

TECHNICAL DATA SHEET

PE-T1002

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant
Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level Insertion Loss = Dissipative Loss + Coupling Loss.

50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts PE-T1002

URL: http://www.pasternack.com/2-way-7-16-equal-tapper-700-mhz-2.7-ghz-700watts-pe-t1002-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE-T1002 CAD Drawing

50 Ohm 2 Way 7/16 DIN Equal Tapper Optimized For Mobile Networks From 700 MHz to 2.7 GHz Rated at 700 Watts

