


剥线尺寸
stripping dimension



产品型号 type	配接电缆 cable type
DSD-J3A	RG316DT

Electrical Characteristics:

- Characteristic Impedance: $50\ \Omega$
- Frequency range: DC~2.0GHz
- Contact resistance
Center conductor: $\leq 5.0\ \text{m}\Omega$
Out conductor: $\leq 2.0\ \text{m}\Omega$
- Insulation resistance: $\geq 500\text{M}\Omega$
- Insulator withstanding: 500V
- VSWR: ≤ 1.4
- Durability: 500cycles

主要性能指标:

- 特性阻抗: $50\ \Omega$
- 频率范围: DC~2.0GHz
- 接触电阻:
中心导体: $\leq 5.0\ \text{m}\Omega$
外导体: $\leq 2.0\ \text{m}\Omega$
- 绝缘电阻: $\geq 500\text{M}\Omega$
- 介质耐压: 500V
- 电压驻波比: ≤ 1.4
- 插拔次数: 500次

Application: Q/FD20131-2006


执行标准: Q/FD20131-2006

Material&Finishing

- Center contact:
Male: brass, gold plated
- Body: brass, gold plated
- Crimp ferrule: copper, gold plated
- Insulators: PTFE

材料和镀层

- 中心接触件:
插针: 黄铜, 镀金
- 壳体: 黄铜, 镀金
- 线夹: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

	SCALE		DSD-J3A RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE <table border="1"> <thead> <tr> <th>FRACTIONS</th> <th>DECIMALS</th> <th>ANGLES</th> </tr> </thead> <tbody> <tr> <td>.X±</td> <td>.15</td> <td>±1°</td> </tr> <tr> <td>.XX±</td> <td>.05</td> <td></td> </tr> <tr> <td>.XXX±</td> <td></td> <td></td> </tr> </tbody> </table>	FRACTIONS	DECIMALS	ANGLES	.X±	.15	±1°	.XX±	.05		.XXX±		
	FRACTIONS	DECIMALS			ANGLES											
.X±	.15	±1°														
.XX±	.05															
.XXX±																
	2.5:1															
	NAME	DATE	西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.													
DRAWN																
CHECKED																
APPROVED																