

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	1	ORIGINAL RELEASE	9/28/09

Description:

Low Noise Amplifier designed for Military and Industrial applications. This amplifier is supplied in our standard PE2 housings in a cascade layout that can be used as a SMA connectorized or a surface mount component. Other packages and connector types are available.

This model provides the following performance. Data is available upon request.

Specifications:

Frequency Range:	0.5 to 2.0 GHz
Gain:	60dB Typ.
Gain Flatness:	+/-1.0dB Max.
Noise Figure:	5.0dB Typ.
OP1dB:	20dBm Min.
VSWR Input/Output:	2.0:1 Max.
DC Voltage Supply:	+12 to +15VDC
DC Current Draw:	430mA Max.

Features:


- Internal Voltage Regulation
- Unconditional Stability
- Standard Operating Temperature -20 to +70 Deg. C

Available Options:

- Various Package types
- Various Connector types
- Temperature Compensation
- Hermetic Sealing
- Gain and Phase Matching
- MIL-STD-883 Screening Available

Environmental Ratings:

- Temperature: -20 to +70 Deg. C (Operating) ; -55 to +85 Deg C Available)
 - 55 to +125 Deg. C (Storage)
 - Humidity: MIL-STD-202F, METHOD 103B COND B.
 - Shock: MIL-STD-202F, METHOD 213B COND B.
 - Altitude: MIL-STD-202F, METHOD 105C COND B.
 - Temperature Cycle: MIL-STD-202F, METHOD 107D COND A
- Note: The above specifications are subject to change or revision.



PART NO.		DATE		TIME	
APPROVALS		9/28/09		PRODUCT FEATURE	
MATERIAL:		DRAWN		CAGE CODE	
6061-T6 Aluminum		K. Mason		DWG NO.	
FINISH:		CHECKED		WEB	
Gold Plate over Nickel		ISSUED		MODEL	
DO NOT SCALE DRAWING				REV.	
				A	

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
± .XX ± 0.010 ±
.XXX ± 0.005

5715 Industry Lane, Unit 11
FREDERICK, MARYLAND