



Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts

TECHNICAL DATA SHEET

PE2215-10

Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts

Co	nfia	uration
		aidioii

Connector 1 SMA Female
Connector 2 SMA Female
Connector 3 SMA Female
Design Directional Coupler

Electrical Specifications

Frequency Range, GHz 2 to 18 Directivity, dB 12 Impedance, Ohms 50 Maximum Insertion Loss, dB 1.3 Maximum Input Power, Watts 25 Maximum Input VSWR 1.35:1 Maximum Secondary Line VSWR 1.5:1 Peak Power, KWatts 3 Coupling Value, dB 10 Coupling Tolerance, dB ± 1 Frequency Sensitivity, dB 0.5

Mechanical Specifications

Size

 Length, in [mm]
 2.85 [72.39]

 Width, in [mm]
 0.38 [9.65]

 Height, in [mm]
 1.2 [30.48]

Connector 1

Type SMA Female

Connector 2

Type SMA Female

Connector 3

Type SMA Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts PE2215-10

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.







Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts

TECHNICAL DATA SHEET

PE2215-10

Plotted and Other Data

Notes:

Values at 25 °C, sea level Directivity: 15 minimum for 2-12.4 GHz, 12 minimum for 12.4-18 GHz

Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts PE2215-10

URL: http://www.pasternack.com/directional-10-db-sma-coupler-2-18-ghz-25-watts-pe2215-10-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE2215-10 CAD Drawing
Directional 10 dB SMA Coupler From 2 GHz to 18 GHz Rated To 25 Watts

