



## 6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz

## TECHNICAL DATA SHEET

PE7365-6

Configuration

Design Fixed, Bidirectional Attenuator Connector 1 SMA Female

Connector 1 SMA Female
Connector 2 TNC Female

Body Material and Plating

Black Anodized Aluminum Heatsink

Electrical Specifications \* Values at 25°C, sea level

Minimum	Typical	Maximum	Units
DC		18	GHz
	50		Ohms
	6 to 6		dB
		25	Watts
		500	Watts
		1.6:1	
		DC 50	DC 18 50 6 to 6 25 500

### Specifications by Frequency

Description	F1	F2	F3	F4	F5	Units
Range	DC to 6	6 to 12.4	12.4 to 18			GHz
VSWR	1.3:1	1.45:1	1.6:1			
Attenuation Accuracy	± 0.5	± 0.75	± 1			dB
Maximum Input Power	25					Watts

### **Mechanical Specifications**

**Temperature** 

Operating Range -55 to +125 deg C

Size

 Length
 4.5 in [114.3 mm]

 Width
 2.41 in [61.21 mm]

 Weight
 0.8 lbs [362.87 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz PE7365-6



ISO 9001: 2008 Registered

PE7365-6 REV 1



# 6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz



## TECHNICAL DATA SHEET

PE7365-6

#### Connectors

Description	Connector 1	Connector 2	
Туре	SMA Female	TNC Female	
Contact Material and Plating	Beryllium Copper, Gold	Beryllium Copper, Gold	
Contact Plating Specification	Gold		
Outer Conductor Material and Plating		Stainless Steel, Passivated	
Coupling Nut Material and Plating	Stainless Steel, Passivated		
Coupling Nut Plating Specification	Stainless Steel		
Hex Size	16-Nov In.	16-Nov In.	
Body Material and Plating	Stainless Steel, Passivated	Stainless Steel, Passivated	
Body Plating Specification	Passivated		

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant

#### Plotted and Other Data

Notes:

Values at 25 °C, sea level

**Performance Data** 

6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz PE7365-6

URL: http://www.pasternack.com/6db-fixed-sma-female-tnc-female-25-watts-attenuator-pe7365-6-p.aspx



# PE7365-6 CAD Drawing

6 dB Fixed Attenuator, SMA Female To TNC Female Black Anodized Aluminum Heatsink Body Rated To 25 Watts Up To 18 GHz

