

# 15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz



### TECHNICAL DATA SHEET

PE7388-15

15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz

Configuration

Design Fixed, Unidirectional Attenuator

Connector 1 N Male
Connector 2 N Female

Body Material and Plating Black Anodized Aluminum Heatsink

**Electrical Specifications** 

Frequency Range, GHz

Impedance, Ohms
50

Attenuation Value, dB
Maximum Input Power, Watts
50

Maximum VSWR
1,25:1

Frequency 1

Range, GHz DC to 3 VSWR 1.25:1 Attenuation Accuracy, dB  $\pm$  0.5

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -55 to +125

Size

 Length, in [mm]
 4.409 [111.99]

 Width, in [mm]
 1.77 [44.96]

 Weight, lbs [g]
 0.54 [244.94]

**Connector 1** 

Type N Male
Contact Material and Plating Brass, Gold
Body Material and Plating Brass, Nickel

Connector 2

Type N Female

Contact Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

**Compliance Certifications** (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heat-sink Body Rated To 50 Watts Up To 3 GHz PE7388-15

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered



## 15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz



### TECHNICAL DATA SHEET

PE7388-15

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level

15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz PE7388-15

URL: http://www.pasternack.com/15db-fixed-n-male-n-female-50-watts-attenuator-pe7388-15-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE7388-15 CAD Drawing

15 dB Fixed Attenuator, N Male To N Female Unidirectional Black Anodized Aluminum Heatsink Body Rated To 50 Watts Up To 3 GHz

