


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 1–50 GHz
 Insertion Loss: 6.4dB Max.
 Isolation: 15dB Min.
 VSWR: 1.75:1 Max.
 Amplitude Balance: ±0.8dB Max.
 Phase Balance: ±9 Deg. Max.
 Power Rating: 16W Avg, 3kW Peak
 Operational Temperature: –32°C to +85°C

MATERIAL:	
DRAWN: Paiboon Luekhamhan	DATE: 04-12-2012
APPROVED: T. Nguyen	DATE: 04-12-2012

	MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
	UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		SHEET: N/A
DRAWING TITLE: <h3>4-WAY POWER DIVIDER</h3>		PART NO. <h2>PS4-200</h2>	
CAGE CODE: OD2L5	SIZE: A	REV: N/A	DWG NO. 86074
DO NOT SCALE THE DRAWING			

PROPRIETARY NOTICE:
 THE INFORMATION IN THIS DRAWING IS PROPRIETARY
 AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN
 PERMISSION FROM MICROWAVE COMMUNICATIONS
 LABORATORIES INC. (MCLI)