



### Electrical Characteristics:

1. Characteristic Impedance:  $50 \Omega$
2. Frequency range: DC~4Ghz
3. Contact resistance  
Center conductor:  $\leq 1.5 \text{ m}\Omega$   
Out conductor:  $\leq 0.2 \text{ m}\Omega$
4. Insulation resistance:  $\geq 5000 \text{ M}\Omega$
5. Insulator withstanding: 1500V
6. Durability: 500cycles

### Application: MIL-C-39012/16E

### Material&Finishing

1. Center contact :  
Female: phosphor bronze, gold plated
2. Bodies and other metal parts:  
brass, nickel plated
3. Insulators: PTFE

### 主要性能指标:

1. 特性阻抗:  $50 \Omega$
2. 频率范围: DC~4Ghz
3. 接触电阻:  
中心导体:  $\leq 1.5 \text{ m}\Omega$   
外导体:  $\leq 0.2 \text{ m}\Omega$
4. 绝缘电阻:  $\geq 5000 \text{ M}\Omega$
5. 介质耐压: 1500V
6. 插拔次数: 500次

### 执行标准: MIL-C-39012/16E

### 材料和镀层

1. 中心接触件:  
插孔: 锡磷青铜, 镀金
2. 壳体和其它金属零件: 黄铜, 镀镍
3. 绝缘子: 聚四氟乙烯

 	SCALE	
	2:1	
	NAME	DATE
DRAWN		
CHECKED		
APPROVED		

BNC-KWF  
RF COAXIAL CONNECTOR

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE mm, TOLERANCES ARE  
FRACTIONS DECIMALS ANGLES  
.X± .15 ±1°  
.XX± .05  
.XXX±

西安富士达科技股份有限公司  
XI'AN FORSTAR S&T CO.,LTD.