

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	A	ORIGINAL RELEASE	09/19/12



DESCRIPTION

PMI MODEL PEC-85-0R32R5-15LM-12-SFF IS A LIMITING AMPLIFIER WITH THE FREQUENCY RANGE OF 0.3 TO 2.5 GHz AND INCLUDES THE FOLLOWING SPECIFICATIONS:

MECHANICAL OUTLINE

SPECIFICATIONS

- FREQUENCY RANGE: 0.3 TO 2.5 GHz
- GAIN: 85dB Typ.
- LIMITED RF OUTPUT: +15dBm, ±2.5dBm
- NOISE FIGURE: 5dB Typ.
- VSWR (INPUT/OUTPUT): 2.0:1 Max.
- SURVIVAL INPUT POWER: +15dBm CW Max.
- OPERATING INPUT POWER: +10dBm CW Max.
- DC SUPPLY: +12VDC WITH INTERNAL VOLTAGE PROTECTION AND REVERSE VOLTAGE PROTECTION.
- FINISH: GOLD PLATED



CONFIDENTIAL & PROPRIETARY



ENVIRONMENTAL RATINGS

- TEMPERATURE: -55°C TO + 85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	A	ORIGINAL RELEASE	09/19/12

MECHANICAL OUTLINE



CONFIDENTIAL & PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001:2000 CERTIFIED



APPROVALS		DATE		TITLE			
DRAWN		09/19/12		OUTLINE DRAWING			
CHECKED				SIZE	FSCM NO.	DWG NO.	REV.
ISSUED				A	05XQ0	27017361	A
				SCALE	N:S	SHEET	1 OF 1