

SMA Female to Reverse Polarity TNC Male Adapter



TECHNICAL DATA SHEET

PE9602

SMA Female to Reverse Polarity TNC Male Adapter

Configuration

Connector 1 SMA Female
Connector Specification 1 MIL-STD-348A
Connector 2 TNC Male
Connector Specification 2 MIL-STD-348A
Adapter Design Standard
Body Style Straight

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Mechanical Specifications

Temperature

Operating Range,deg C -65 to +165

Size

Length, in [mm] 1.05 [26.67] Width/Dia., in [mm] 0.59 [14.99]

Connector 1

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

Connector 2

Type TNC Male

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-tnc-male-straight-adapter-pe9602-p.aspx

SMA Female to Reverse Polarity TNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9602 CAD DrawingSMA Female to Reverse Polarity TNC Male Adapter

