


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS:

Frequency Range: 6–12 GHz
 Isolation: 17dB Min.
 Insertion Loss: 0.7 dB Max.
 VSWR: 1.35:1 Max.
 Power Avg/Peak: 25 Watts / 250W
 Operating Temperature: –54°C TO +85°C

MATERIAL: 		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$		DRAWING TITLE: COAXIAL ISOLATOR			
		PART NO. IS-24			
DRAWN: Paiboon Luekhamhan		DATE: 08-06-2001		CAGE CODE: OD2L5	
APPROVED: T. Nguyen		DATE: 08-06-2001		SIZE: N/A	
				REV: N/A	
				DWG NO. 82112	
				DO NOT SCALE THE DRAWING	