

DESCRIPTION

PMI MODEL P1T-10M1G-80-T-SFF IS AN ABSORPTIVE, HIGH SPEED, SINGLE POLE SINGLE THROW SWITCH CAPABLE OF SWITCHING WITHIN 200 ns MAXIMUM. THE FREQUENCY RANGE IS 0.010 GHz TO 1.0 GHz. THIS SWITCH HAS > 80 dB ISOLATION.

SPECIFICATIONS

- FREQUENCY RANGE: _____ 0.01 GHz TO 1.0 GHz
- IMPEDANCE: _____ 50 Ω
- INPUT POWER: _____ +30dBm MAX (SURVIVAL)
_____ +20dBm MAX (OPERATING)
- INPUT VSWR: _____ 1.5:1 TYP.
- INSERTION LOSS: _____ 1.3dB MAX
- ISOLATION: _____ 80dB TYP.
- SWITCHING SPEED: _____ 200ns MAX
- DC VOLTAGE: _____ +5VDC, 20mA TYP.
_____ -15VDC, 40mA TYP.
- CONTROL: _____ SOLDER PIN
TTL COMPATIBLE
"0" = INSERTION LOSS
"1" = ISOLATION
- CONNECTORS IN/OUT: _____ SMA (F)
- SIZE: _____ (L) 1.0" X (W) 1.0" X (H) 0.5"
- FINISH: _____ BLUE EPOXY POLIMIDE COATING IAW MIL-C-22750, TYPE I OVER EPOXY POLIMIDE PRIMER IAW MIL-P-23377, TYPE I, CLASS 1 OR 3.


ENVIRONMENTAL RATINGS

- **TEMPERATURE:** ————— -55°C TO + 85°C (OPERATING)
—65°C TO +125°C (STORAGE)
- **HUMIDITY:** ————— MIL-STD-202F, METHOD 103B COND. B
- **SHOCK:** ————— MIL-STD-202F, METHOD 213B COND. B
- **VIBRATION:** ————— MIL-STD-202F, METHOD 204D COND. B
- **ALTITUDE:** ————— MIL-STD-202F, METHOD 105C COND. B
- **TEMPERATURE CYCLE:** ——— MIL-STD-202F, METHOD 107D COND. A

NOTE: SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE
NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	1	PRELIMINARY	9/25/15	

MECHANICAL OUTLINE



PMI CONFIDENTIAL AND PROPRIETARY

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-rf.com
E-MAIL: sales@pmi-rf.com
ISO 9001 CERTIFIED



ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.020
X.XXX ±0.010

APPROVALS		DATE	TITLE PRODUCT FEATURE P1T-10M1G-80-T-SFF			
DRAWN <i>B. Thomas</i>		<i>9/25/15</i>				
CHECKED						
ISSUED			SIZE A	FSCM NO. 05XQ0	DWG NO. 27026281	REV 1
			SCALE N:S		SHEET 1 OF 1	