


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED

SPECIFICATIONS

FREQUENCY RANGE: 5.8–6.45 GHz
 INSERTION LOSS: 1.9dB Max.
 ISOLATION: 60dB Min.
 VSWR: 1.95:1 Max.
 INPUT POWER: 200 mW (23 dBm)
 SWITCHING TIME: 100 nSEC



Driver Schottky TTL
 Voltage/Current Required:
 +5 Vdc @ +120 mA, Typical
 -5 Vdc @ -50 mA, Typical

Higher speeds available.
 Individual TTL Control Logic:
 "0" (-0.3V to +0.8V) = ON
 "0" (+2.0V to +5.0V) = OFF

MATERIAL:			MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A
					SHEET:	N/A
DRAWN: Paiboon Luekhamhan DATE: 04-20-2009		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm .02 \pm .008$ ANGLE: $\pm 1/2^\circ$	DRAWING TITLE:			
			SP8T PIN DIODE SWITCHES			
APPROVED: T. Nguyen DATE: 04-20-2009		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)	PART NO.			
			D8-12			
			CAGE CODE:	SIZE:	REV:	DWG NO.
			OD2L5	A	N/A	84382
DO NOT SCALE THE DRAWING						