




Electrical Characteristics:

1. Characteristic Impedance: 50Ω
2. Frequency range: DC~7.5GHz
3. Contact resistance
Center conductor: $\leq 1.0\text{ m}\Omega$
Out conductor: $\leq 0.5\text{ m}\Omega$
4. Insulation resistance: $\geq 10000\text{ M}\Omega$
5. Insulator withstanding: 4000V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50Ω
2. 频率范围: DC~7.5GHz
3. 接触电阻:
中心导体: $\leq 1.0\text{ m}\Omega$
外导体: $\leq 0.5\text{ m}\Omega$
4. 绝缘电阻: $\geq 10000\text{ M}\Omega$
5. 介质耐压: 4000V
6. 插拔次数: 500次

Application: IEC 60169-4

执行标准: IEC 60169-4

Material & Finishing

1. Center contact :
Female: phosphor bronze, silver plated
2. Bodies: brass, SUCO plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 锡磷青铜, 镀银
2. 壳体: 黄铜, 镀三元合金
3. 绝缘子: 聚四氟乙烯

 	SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	1.5:1		
	NAME	DATE	L29-KFD21 RF COAXIAL CONNECTOR 西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO., LTD.
DRAWN			
CHECKED			
APPROVED			