

FREQUENCY SYNTHESIZER

441052

800 - 900 MHz

Features

- Low Phase Noise
- Low Spurious Outputs
- High Reliability
- External Reference Model

Specifications


CHARACTERISTIC	TYPICAL Ta = +25 °C	MIN/MAX Ta = -10°C to +60 °C
Frequency (MHz)	800 - 900	800 - 900
Output Power (dBm)	+13	0 / +17.0
Step Size	1 MHz	1 Hz / 10 MHz
Reference (MHz)	10	1 - 200
Harmonics (dBc)	-25	-20 Max.
Spurious (dBc)	-70	—
Phase Noise (800 MHz)	-73 dBc/Hz @ 10 Hz -78 dBc/Hz @ 100 Hz -81 dBc/Hz @ 1 kHz -82 dBc/Hz @ 10 kHz -111 dBc/Hz @ 100 kHz -130 dBc/Hz @ 1 MHz	—
Power	Vdc mA	+15 150

NOTE: Care should always be taken to effectively ground the case of each unit.

Spectrum Microwave can design a synthesizer to meet your requirements, from low-cost surface mount commercial units to complex multiple conversion designs for military and space applications.


We have delivered units with step sizes from 0.002 Hz to 200 MHz, 5-microsecond switching speeds, automatically switched back-up references, direct digital synthesis, and many other special features.

Typical Performance Data



Absolute Maximum (No Damage) Ratings

Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +24 Volts



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532

Rev.
3/29/10

www.SpectrumMicrowave.com Spectrum Microwave · 2707 Black Lake Place · Philadelphia, Pennsylvania 19154 · PH (215) 464-4000 · Fax (215) 464-4001