



产品型号 type	L1	L2	d
SMA-KHD2	6.1	1.5	Ø1.3
SMA-KHD3	6.7	2.2	Ø0.8
SMA-KHD5	6.5	2.0	Ø0.8

Electrical Characteristics:

- Characteristic Impedance: 50 Ω
- Frequency range: DC~18Ghz
- Contact resistance
Center conductor: ≤3.0 mΩ
Out conductor: ≤2.0 mΩ
- Insulation resistance: ≥5000MΩ
- Insulator withstanding: 1000V
- Durability: 500cycles

Application: MIL-C-39012/55D

Accordance With ROHS Exemption

Material&Finishing

- Center contact :
Female: beryllium copper, gold plated
- Body: brass, gold plated
- Insulators: PTFE

主要性能指标:

- 特性阻抗: 50 Ω
- 频率范围: DC~18Ghz
- 接触电阻:
中心导体: ≤3.0 mΩ
外导体: ≤2.0 mΩ
- 绝缘电阻: ≥5000MΩ
- 介质耐压: 1000V
- 插拔次数: 500次

执行标准: MIL-C-39012/55D

符合ROHS指令要求

材料和镀层

- 中心接触件:
插孔: 镀青铜, 镀金
- 壳体: 黄铜, 镀金
- 绝缘子: 聚四氟乙烯

 	SCALE	SMA-KHD2 RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
	2.5:1		
NAME	DATE		
DRAWN			
CHECKED			
APPROVED			

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.