

REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	-	ORIGINAL RELEASE	9/28/09

Description:

Low Noise Amplifier designed for Military and Industrial applications. This amplifier is supplied in our standard PE2 housings in a cascade layout that can be used as a SMA connectorized or a surface mount component. Other packages and connector types are available.

This model provides the following performance. Data is available upon request.

Specifications:

- Frequency Range:
Gain:
Gain Flatness:
Noise Figure:
OP1dB:
VSWR Input/Output:
DC Voltage Supply:
DC Current Draw:
- 1.0 to 1.5 GHz
60dB Typ.
+/-0.75dB Max.
4.5dB Typ.
13dBm Min.
2.0:1 Max.
+12 to +15VDC
280mA Max.

Features:


- Internal Voltage Regulation
- Unconditional Stability
- Standard Operating Temperature -20 to +70 Deg. C

Available Options:

- Various Package types
- Various Connector types
- Temperature Compensation
- Hermetic Sealing
- Gain and Phase Matching
- MIL-STD-883 Screening Available

Environmental Ratings:

- Temperature:
Humidity:
Shock:
Altitude:
Temperature Cycle:
- 20 to +70 Deg. C (Operating) ; -55 to +85 Deg C Available)
-55 to +125 Deg. C (Storage)
MIL-STD-202F, METHOD 103B COND B.
MIL-STD-202F, METHOD 213B COND B.
MIL-STD-202F, METHOD 105C COND B.
MIL-STD-202F, METHOD 107D COND A
- Note: The above specifications are subject to change or revision.



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		PART NO.		 5715 Industry Lane, Unit 11 FREDERICK, MARYLAND
		APPROVALS	DATE	
TOLERANCES ARE: FRACTIONS DECIMALS ANGLES	MATERIAL:	DRAWN	9/28/09	TITLE PRODUCT FEATURE PE2-60-1R01RS-4RS-15-12-SFF-WEB
	6061 - T6 Aluminum	K. Mason		
	FINISH:	CHECKED		
± .XX ± 0.010	ANGLES	ISSUED		SIZE CAGE CODE DWG NO.
.XXX ± 0.005	±			B 1LK53 WEB - MODEL REV.
				SCALE N/A SHEET 1 OF 1

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
± .XX ± 0.010 ±
.XXX ± 0.005

5715 Industry Lane, Unit 11
FREDERICK, MARYLAND

PRODUCT FEATURE

PE2-60-1R01R5-4R5-15-12-SFF-WEB

SIZE B 1LK53

SCALE N/A

WEB - MODEL A

SHEET 1 OF 1