



TNC Female Precision Connector Solder Attachment For PE-SR402AL, PE-SR402FL, PE-SR402FLJ, RG402

TECHNICAL DATA SHEET

PE44713

TNC Female Precision Connector Solder Attachment For PE-SR402AL, PE-SR402FL, PE-SR402FLJ, RG402

Configuration

Connector TNC Female

Connector Interface Type PE-SR402AL,PE-SR402FLJ,RG402

Cable Attachment Method (Shield/Contact)

Connector Design

Body Style

Solder/Solder

Precision

Straight

Electrical Specifications

Frequency Range, GHz DC to 6 Impedance, Ohms 50

Mechanical Specifications

Size

Length, in [mm] 0.831 [21.11] Width/Dia., in [mm] 0.472 [11.99]

Connector

Type TNC Female

Contact Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

TNC Female Precision Connector Solder Attachment For PE-SR402AL, PE-SR402FL, PE-SR402FLJ, RG402 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Female Precision Connector Solder Attachment For PE-SR402AL, PE-SR402FL, PE-SR402FLJ, RG402 PE44713

URL: http://www.pasternack.com/tnc-female-standard-pe-sr402al-pe-sr402fl-pe-sr402fli-connector-pe44713-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44713 CAD Drawing

TNC Female Precision Connector Solder Attachment For PE-SR402AL, PE-SR402FL, PE-SR402FLJ, RG402

