


REVISIONS				
ZONE	REV	DESCRIPTION	Date	APPROVED



SPECIFICATIONS

Frequency Range: 1.2–1.5 GHz
 Isolation: 23dB Min.
 Insertion loss: 0.50dB Max.
 VSWR: 1.15:1 Max.
 Operating Temperature: 0°C to +55°C
 Power: 50W Avg, 100W Peak

MATERIAL:		MCLI		MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE:	N/A						
						SHEET:	N/A						
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±.01 ±.005 ANGLE: ±1/2°		DRAWING TITLE: CIRCULATOR									
				PART NO. CS-53									
		DRAWN: Paiboon Luekhamhan		DATE: 11-14-2011		CAGE CODE: OD2L5		SIZE: N/A		REV: A		DWG NO. 84843	
		APPROVED: T. Nguyen		DATE: 11-14-2011				DO NOT SCALE THE DRAWING					
				THIRD ANGLE PROJECTION									