



SMA Male to TNC Female Bulkhead Semi-Flexible
Precision Cable Using PE-SR405FL Coax, RoHS

TECHNICAL DATA SHEET

PE39475

Pasternack's formable cable assemblies are hand formable semi-rigid replacements that are an alternative to costly preformed assemblies. The formable semi-rigid cable alternatives are dimensionally and electrically similar to their semi-rigid counterpart and have a tinned-copper-braid outer shield that provides excellent RF shielding. The hand formable cable assemblies from Pasternack do not require special tooling to shape or reshape the assemblies and can replace standard semi-rigid versions. The assemblies are available with or without a FEP jacket and are RoHS compliant,

Features

- Dimensionally and electrically the same as standard, solid outer conductor semi-rigid coax
- Cable may be formed by hand and does not require special tools to bend
- May be formed more than once without damaging the outer conductor
- High RF Shielding >100 dB
- 100% Hi-pot and continuity tested
- 100% VSWR tested to max frequency of assembly
- Standard and custom lengths ship the same day

Configuration

Connector 1
Connector 2
Cable Type

SMA Male
TNC Female Bulkhead
PE-SR405FL

Electrical Specifications

Frequency Range
Impedance
Velocity of Propagation

DC to 6 GHz
50 Ohms
69.5 %

Performance by Frequency

Frequency 1

Frequency
Insertion Loss

250 MHz
0.256 dB/ft [0.84 dB/m]

Frequency 2

Frequency
Insertion Loss

500 MHz
0.313 dB/ft [1.03 dB/m]

Frequency 3

Frequency
Insertion Loss

1000 MHz
0.425 dB/ft [1.39 dB/m]

Frequency 4

Frequency
Insertion Loss

2.5 GHz
0.547 dB/ft [1.79 dB/m]

Frequency 5

Frequency
Insertion Loss

6 GHz
0.802 dB/ft [2.63 dB/m]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to TNC Female Bulkhead Semi-Flexible Precision Cable Using PE-SR405FL Coax, RoHS PE39475](#)



SMA Male to TNC Female Bulkhead Semi-Flexible
Precision Cable Using PE-SR405FL Coax, RoHS

TECHNICAL DATA SHEET

PE39475

Mechanical Specifications

Size

Diameter 0.69 in [17.53 mm]

Cable

Cable Type PE-SR405FL
Inner Conductor Type Solid
Cable Inner Conductor Copper Clad Steel, Silver
No of Shields 1
Dielectric Type PTFE

Connector 1

Type SMA Male
Configuration Straight
Inner Conductor Material and Plating Brass, Gold
Coupling Nut Material and Plating Passivated Stainless Steel
Hex Size 5/16 in.
Torque 8 in-lbs [0.9 Nm]
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Connector 2

Type TNC Female Bulkhead
Configuration Straight
Mount Method Bulkhead
Inner Conductor Material and Plating Beryllium Copper, Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes
REACH Compliant 12/15/2010

Plotted and Other Data

Notes:

- Values at +25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to TNC Female Bulkhead Semi-Flexible Precision Cable Using PE-SR405FL Coax, RoHS PE39475](#)



SMA Male to TNC Female Bulkhead Semi-Flexible
Precision Cable Using PE-SR405FL Coax, RoHS

TECHNICAL DATA SHEET

PE39475

How to Order

Part Number Configuration:

PE39475

- xx

uu

Unit of Measure:
cm = Centimeters
<blank> = Inches
Length
Base Number

Example: PE39475-12 = 12 inches long cable
PE39475-100cm = 100 cm long cable

SMA Male to TNC Female Bulkhead Semi-Flexible Precision Cable Using PE-SR405FL Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to TNC Female Bulkhead Semi-Flexible Precision Cable Using PE-SR405FL Coax, RoHS PE39475](http://www.pasternack.com/sma-male-tnc-female-pe-sr405fl-cable-assembly-pe39475-p.aspx)

URL: <http://www.pasternack.com/sma-male-tnc-female-pe-sr405fl-cable-assembly-pe39475-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE39475 CAD Drawing

SMA Male to TNC Female Bulkhead Semi-Flexible Precision Cable Using PE-SR405FL Coax, RoHS



Note: This part is lead free.



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $3/8"$, WHICHEVER IS GREATER.

DWG TITLE

PE39475

FSCM NO. 53919

CAD FILE

012215

SCALE N/A

SIZE A

2233