

50 Ohm 2 Watts Precision Passivated Stainless Steel SMA Male RF Load Up To 18 GHz



TECHNICAL DATA SHEET

PE6081

50 Ohm 2 Watts Precision Passivated Stainless Steel SMA Male RF Load Up To 18 GHz

Configuration

Connector DesignPrecisionConnectorSMA MaleBody StyleStraight

Electrical Specifications

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

Maximum Input Power, Watts

DC to 18

1.3:1

2

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +125

Size

 Length, in [mm]
 0.58 [14.73]

 Width/Dia., in [mm]
 0.312 [7.92]

 Weight, lbs [g]
 0.008 [3.63]

Connector

Type SMA Male Inner Conductor Material and Plating Beryllium C

Inner Conductor Material and Plating

Outer Conductor Material and Plating

Coupling Nut Material and Plating

Beryllium Copper, Gold

Passivated Stainless Steel

Passivated Stainless Steel

 Hex Size, Inch
 5/16

 Torque, in-lbs [Nm]
 8 [0.9]

Body Material and Plating Passivated Stainless Steel

Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/2-watts-sma-male-rf-load-up-to-18-ghz-precision-pe6081-p.aspx

50 Ohm 2 Watts Precision Passivated Stainless Steel SMA Male RF Load Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

