



## D-Sub Receptacle Contact Solder Attachment Thru Hole PCB, .200 inch x .046 inch Hole Spacing

## TECHNICAL DATA SHEET

PE4832

## D-Sub Receptacle Contact Solder Attachment Thru Hole PCB, .200 inch x .046 inch Hole Spacing

Configuration

Connector D-Sub Receptacle
Connector Interface Type Thru Hole

Cable Attachment Method (Shield/Contact)

Solder

Body Style

Straight

**Electrical Specifications** 

Impedance, Ohms 50

**Mechanical Specifications** 

Size

 Length, in [mm]
 0.67 [17.02]

 Width/Dia., in [mm]
 0.224 [5.69]

 Weight, lbs [g]
 0.006 [2.72]

Connector

Type D-Sub Receptacle

Contact Material and Plating
Outer Conductor Material and Plating
Body Material and Plating
Dielectric Type
Gold
Brass, Gold
Brass, Gold
PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes: Values at 25 °C, sea level

D-Sub Receptacle Contact Solder Attachment Thru Hole PCB, .200 inch x .046 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: D-Sub Receptacle Contact Solder Attachment Thru Hole PCB, .200 inch x .046 inch Hole Spacing PE4832

URL: http://www.pasternack.com/d-sub-receptacle-standard-thru-hole-pcb-connector-pe4832-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## PE4832 CAD Drawing

D-Sub Receptacle Contact Solder Attachment Thru Hole PCB, .200 inch x .046 inch Hole Spacing

