



50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant

TECHNICAL DATA SHEET

PE7070

50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant

Configuration

Design Fixed Matching Pad

Body Style Straight
Connector 1 N Male
Impedance 1 50 Ohms
Connector Specification 1 MIL-STD-348

Connector Specification 1

Connector 2

Impedance 2

Connector Specification 2

MIL-STD-348

N Female

75 Ohms

MIL-STD-348

Electrical Specifications

Frequency Range, GHz

Maximum VSWR

1.35:1

Maximum Attenuation, dB

Attenuation Accuracy

Maximum Input Power, Watts

Peak Power, Watts

Peak Power Duty Cycle, µs

DC to 3

1.35:1

5.7

4.05

1.05

2.50

5.06

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

1.07

Directionality Bidirectional

Mechanical Specifications

Temperature

Operating Range, deg C -20 to +85

Size

Length, in [mm] 1.91 [48.51] Width/Dia., in [mm] 0.8 [20.32]

Connector 1

Type N Male

Connector 2

Type N Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant PE7070

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant

TECHNICAL DATA SHEET

PE7070

Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant PE7070

URL: http://www.pasternack.com/50-ohm-n-male-75-ohm-n-female-matching-pad-pe7070-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7070 CAD Drawing

50 Ohm N Male To 75 Ohm N Female Matching Pad Operating From DC to 3 GHz RoHS Compliant

