

AD-C3N8	C Plug To N Jack	50Ω																											
Technical drawing of the AD-C3N8 connector. The drawing shows a side view of the assembly with the following dimensions: Outer diameter: Ø19 (Ø.748). Total length: 32.6 (1.283). Thread specification: 5/8-24UNEF-2A.																													
Typical VSWR <table><tr><td>Part Number</td><td>1Ghz</td><td>2 Ghz</td><td>3Ghz</td><td>4Ghz</td></tr><tr><td>AD-C3N8</td><td>1.04</td><td>1.07</td><td>1.1</td><td>1.2</td></tr></table>			Part Number	1Ghz	2 Ghz	3Ghz	4Ghz	AD-C3N8	1.04	1.07	1.1	1.2																	
Part Number	1Ghz	2 Ghz	3Ghz	4Ghz																									
AD-C3N8	1.04	1.07	1.1	1.2																									
<table><tr><td>Parts</td><td>Material</td><td>Plating (Micro-inch)</td></tr><tr><td>Washer</td><td>Brass</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr><tr><td>Spring</td><td>SK5</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr><tr><td>Contact Pin</td><td>Beryllium Copper</td><td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td></tr><tr><td>Insulator</td><td>Teflon</td><td></td></tr><tr><td>Center Body</td><td>Brass</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr><tr><td>Body</td><td>Brass</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr><tr><td>Ferrule</td><td>Brass</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr><tr><td>Coupling Nut</td><td>Brass</td><td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td></tr></table>			Parts	Material	Plating (Micro-inch)	Washer	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Spring	SK5	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Center Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Ferrule	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Parts	Material	Plating (Micro-inch)																											
Washer	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Spring	SK5	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																											
Insulator	Teflon																												
Center Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Ferrule	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																											
Weight:																													

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.